

ESD-133-T-25

ESD-133-T-25 Information

Heisener com Description Part Number Manufacturer Category		ESD-133-T-25 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED SOCKET STRIPS		
For Reference Only		For the pricing/inventory/lead time, please contact us		
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESD-133-T-25 Specifications

Manufacturer Part NumberESD-133-T-25ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESDConnector TypeElevated SocketContact TypeFemale SocketStyleBoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Loaded10µin (0.25µm)Contact Finish Thickness - Mating0.106" (1.70mm)Contact Finish Thickness - Mating0.500" (1.270mm)Contact Finish Thickness - Mating0.500" (1.270mm)Contact Length - Post0.55° C ~ 125°CMaterial Elammability Rating1194 V-0		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESDConnector TypeElevated SocketContact TypeBoard to BoardNumber of Positions66Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeInfoug HoleYoung TypeSolderFreminationSolderFreminationSolderForta Finish - MatingGoldContact Finish - MatingInjun (0.25µm)Forta Finish Thickness - MatingInjun (0.25µm)Insulation ColorBlackInsulation Finish Thickness - MatingIopin (0.25µm)Insulation Finish Thickness - MatingIopin (0.25µm)Insulat	Manufacturer Part Number	ESD-133-T-25
Ackage . Series ESD Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 66 Number of Positions Loaded All Prich - Mating 0.100° (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100° (2.54mm) Mounting Type Through Hole Yourd Acting Solder Forniation Solder Contact Finish - Mating Gold Contact Finish - Mating Gold Solare Injun (0.25µm) Fastening Type Push-Pull Contact Finish - Mating Gold Solare Injun (0.25µm) Insulation Color Black Insulation Height 0.500° (12.70mm) Solor (12.70mm) Golder Solare Solare Solare Solare Solare Solare Solare Solare Solare Solare	Manufacturer	Samtec Inc.
Package-SeriesESDConnector TypeElevated SocketContact TypeFenale SocketStyleBoard to BoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating1.010° (2.54mm)Mounting Type0.100° (2.54mm)Young TypeSolderTerminationSolderFastening TypeOldContact Finish - MatingGoldContact Finish - MatingIojm (0.25µm)Insulation ColorBlackInsulation Finish - MatingSolor (1.20mm)Contact Finish Type0.50° (1.20mm)Contact Finish TypeSolor (1.20mm)Insulation Finish - MatingSolor (1.20mm)Contact Finish TypeSolor (1	Category	Connectors, Interconnects
SeriesESDConnector TypeElevated SocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeOlono" (2.54mm)TerminationSolderFastening TypeOlono" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingIpuin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeFemale SocketStyleBoard to BoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingIopin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeFemale SocketStyleBoard to BoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.90" (2.5µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Series	ESD
StyleBoard to BoardNumber of Positions66Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 66 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type 0.100" (2.54mm) Termination 0.100" (2.54mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.500" (12.70mm) Contact Length - Post 0.165" (4.19mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIbuin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Number of Positions	66
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.500" (12.70mm) Contact Length - Post 0.165" (4.19mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.500" (12.70mm) Contact Length - Post 0.165" (4.19mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post0.165" (4.19mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.500" (12.70mm)
	Contact Length - Post	0.165" (4.19mm)
Material Flammability Rating UI.94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin		
Mated Stacking Heights	-		
Ingress Protection	-		
Features	-		
		Report	errors?

ESD-133-T-25 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESD-133-T-25, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com