



ESM25DSEH Information

Heisener.com

Part Number ESM25DSEH

ManufacturerSullins Connector SolutionsCategoryConnectors, Interconnects

Card Edge Connectors - Edgeboard Connectors

Description CONN EDGE DUAL FMALE 50POS 0.156

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESM25DSEH Specifications

Manufacturer Part Number ESM25DSEH Manufacturer Sullins Connector Solutions Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Contact Material Phosphor Bronze Contact Hinish Thickness Gold Contact Finish Thickness 10µin (0.25µm) Cotor Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	ESWI23DSEII Speemeations	
Category Connectors, Interconnects Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer Part Number	ESM25DSEH
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.155" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Type Full Bellows Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package - Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Category	Connectors, Interconnects
Series - Card Type Non Specified - Dual Edge Gender Female Number of Positions/Bay/Row 25 Number of Positions 50 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features - Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Cotact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row 25 Number of Positions 50 Card Thickness $0.062"$ ($1.57mm$)Number of Rows 2 Pitch $0.156"$ ($3.96mm$)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness $10\mu in (0.25\mu m)$ Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, $0.125"$ ($3.18mm$) DiaOperating Temperature $-65°C \sim 125°C$	Series	-
Number of Positions/Bay/Row25Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions50Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10µin (0.25µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Gender	Female
Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.156" (3.96mm) Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness 10µin (0.25µm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Positions/Bay/Row	25
Number of Rows2Pitch $0.156"$ (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, $0.125"$ (3.18mm) DiaOperating Temperature -65° C ~ 125° C	Number of Positions	50
Pitch0.156" (3.96mm)Features-Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness10μin (0.25μm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
Features Mounting Type Panel Mount Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Contact Finish Thickness 10μin (0.25μm) Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Number of Rows	2
Mounting TypePanel MountTerminationSolder Eyelet(s)Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125" (3.18mm) DiaOperating Temperature -65 °C ~ 125 °C	Pitch	0.156" (3.96mm)
Termination Solder Eyelet(s) Contact Material Phosphor Bronze Contact Finish Gold Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125 " ($3.18mm$) Dia Operating Temperature -65 °C ~ 125 °C	Features	-
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness 10μ in $(0.25\mu$ m)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Unthreaded, 0.125 " $(3.18$ mm) DiaOperating Temperature -65 °C ~ 125 °C	Mounting Type	Panel Mount
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Termination	Solder Eyelet(s)
Contact Finish Thickness $10\mu in (0.25\mu m)$ Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Material	Phosphor Bronze
Contact Type Full Bellows Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish	Gold
Color Blue Flange Feature Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia Operating Temperature -65°C ~ 125°C	Contact Finish Thickness	10μin (0.25μm)
Flange Feature Top Mount Opening, Unthreaded, 0.125 " (3.18mm) Dia Operating Temperature -65 °C ~ 125 °C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Color	Blue
	Flange Feature	Top Mount Opening, Unthreaded, 0.125" (3.18mm) Dia
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

ESM25DSEH Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESM25DSEH Payment Methods



















ESM25DSEH Shipping Methods













If you have any question about ESM25DSEH, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com