

# ESMQ161ELL331MMP1S

## ESMQ161ELL331MMP1S Information



### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# ESMQ161ELL331MMP1S Specifications

ManufacturerUnder Chemi-ConCapacitorsCapacitorsPackageRadial, CanPackageSMQCapacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature9001 Hrs @ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.457° (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, CanSeriesSMQCapacitance30µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationGeneral PurposeApplicationsGeneral PurposeRipple Current - Low Frequency95mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.457° (37.00mm)Surface Mount Land Size-Package / CaseKadia, Can	Manufacturer Part Number	ESMQ161ELL331MMP1S
Aluminum Electrolytic CapacitorsPackageRadial, CanSeriesSMQCapacitance330µFTolerance±20%Voltage - Rated60VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRipple Current - Low Frequency995mA @ 120HzRipple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension1.457° (37.00mm)Height - Seated (Max)1.457° (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Manufacturer	United Chemi-Con
PackageRadial, CanSeriesSMQCapacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature40°C ~ 85°CPolarizationGeneral PurposeRiple Current - Low Frequency995mA @ 120HzRiple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.457° (37.00mm)Surface Mount Land Size-Package / CaseRadial, Can	Category	Capacitors
SeriesSMQCapacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRatial, Can		Aluminum Electrolytic Capacitors
Capacitance330µFTolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Pokage / CaseRadial, Can	Package	Radial, Can
Tolerance±20%Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarrPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzImpedance-Lead Spacing0.295° (7.50mm)Size / Dimension0.709° Dia (18.00mm)Height - Seated (Max)1.457° (37.00mm)Surface Mount Land Size-Pokage / CaseRatial, Can	Series	SMQ
Voltage - Rated160VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency95mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension1.4925 (300mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFarcage / CasePackage / CaseRatial, Can	Capacitance	330µF
Constraint-ESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeRadial, Can	Tolerance	±20%
Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFolge HolePackage / CaseRadial, Can	Voltage - Rated	160V
Operating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzRipple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeFnough HolePackage / CaseRadial, Can	ESR (Equivalent Series Resistance)	-
PolarizationPolarPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzRipple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lifetime @ Temp.	2000 Hrs @ 85°C
ApplicationsGeneral PurposeRipple Current - Low Frequency995mA @ 120HzRipple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency995mA @ 120HzRipple Current - High Frequency1.4925A @ 100kHzImpedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Polarization	Polar
In a constraint of the formula of t	Applications	General Purpose
Impedance-Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - Low Frequency	995mA @ 120Hz
Lead Spacing0.295" (7.50mm)Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Ripple Current - High Frequency	1.4925A @ 100kHz
Size / Dimension0.709" Dia (18.00mm)Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Impedance	-
Height - Seated (Max)1.457" (37.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Lead Spacing	0.295" (7.50mm)
Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can	Size / Dimension	0.709" Dia (18.00mm)
Mounting TypeThrough HolePackage / CaseRadial, Can	Height - Seated (Max)	1.457" (37.00mm)
Package / Case Radial, Can	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can
		Report errors?

# ESMQ161ELL331MMP1S Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### ESMQ161ELL331MMP1S Payment Methods



If you have any question about ESMQ161ELL331MMP1S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com