

Heisener.com

ESMQ201VSN561MQ25W

ESMQ201VSN561MQ25W Information

Part Number ESMQ201VSN561MQ25W

Manufacturer United Chemi-Con

Capacitors Category

Aluminum Electrolytic Capacitors

CAP ALUM 560UF 20% 200V SNAP **Description**

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESMQ201VSN561MQ25W Specifications

Manufacturer Part Number ESMQ201VSN561MQ25W Manufacturer United Chemi-Con Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series SMQ Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESK (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series SMQ Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer Part Number	ESMQ201VSN561MQ25W
Package Radial, Can - Snap-In Series SMQ Capacitance 560µF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Manufacturer	United Chemi-Con
Package Radial, Can - Snap-In Series SMQ Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Category	Capacitors
Series SMQ Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In		Aluminum Electrolytic Capacitors
Capacitance 560μF Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Package	Radial, Can - Snap-In
Tolerance ±20% Voltage - Rated 200V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Series	SMQ
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Capacitance	560μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 2.43 A @ 120 Hz Ripple Current - High Frequency 3.645 A @ 50 k Hz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency 3.645A @ 50kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 2000 Hrs @ 85°C -25°C ~ 85°C Folarization Polar General Purpose 2.43A @ 120Hz 3.645A @ 50kHz	Voltage - Rated	200V
Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 2.43A @ 120Hz Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications General Purpose Ripple Current - Low Frequency 2.43 A @ 120Hz Ripple Current - High Frequency 3.645 A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 3.645A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Polarization	Polar
Ripple Current - High Frequency Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case 3.645A @ 50kHz - 0.394" (10.00mm) 1.000" Dia (25.40mm) 1.063" (27.00mm) Through Hole Radial, Can - Snap-In	Applications	General Purpose
Impedance - Case	Ripple Current - Low Frequency	2.43A @ 120Hz
Lead Spacing 0.394" (10.00mm) Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Ripple Current - High Frequency	3.645A @ 50kHz
Size / Dimension 1.000" Dia (25.40mm) Height - Seated (Max) 1.063" (27.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Lead Spacing	0.394" (10.00mm)
Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Size / Dimension	1.000" Dia (25.40mm)
Mounting Type Through Hole Package / Case Radial, Can - Snap-In	Height - Seated (Max)	1.063" (27.00mm)
Package / Case Radial, Can - Snap-In	Surface Mount Land Size	-
	Mounting Type	Through Hole
Report errors?	Package / Case	Radial, Can - Snap-In
*		Report errors?

ESMQ201VSN561MQ25W Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESMQ201VSN561MQ25W Payment Methods



















ESMQ201VSN561MQ25W Shipping Methods













If you have any question about ESMQ201VSN561MQ25W, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com