

# ESMQ251VSN102MA30S

### ESMQ251VSN102MA30S Information



For Reference Only

Part Number ESMQ251VSN102MA30S

Manufacturer United Chemi-Con

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 1000UF 20% 250V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

#### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ESMQ251VSN102MA30S Specifications

Manufacturer Part Number         ESMQ251VSN102MA30S           Manufacturer         United Chemi-Con           Category         Capacitors           Package         Radial, Can - Snap-In           Series         SMQ           Capacitance         1000μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         3.32A @ 120Hz           Ripple Current - High Frequency         4.98A @ 50kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)		
Category         Capacitors           Package         Radial, Can - Snap-In           Series         SMQ           Capacitance         1000µF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         3.32A @ 120Hz           Ripple Current - High Frequency         4.98A @ 50kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)	Manufacturer Part Number	ESMQ251VSN102MA30S
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - Snap-InSeriesSMQCapacitance1000μFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.32A @ 120HzRipple Current - High Frequency4.98A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)	Manufacturer	United Chemi-Con
Package         Radial, Can - Snap-In           Series         SMQ           Capacitance         1000μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         3.32A @ 120Hz           Ripple Current - High Frequency         4.98A @ 50kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)	Category	Capacitors
Series         SMQ           Capacitance         1000μF           Tolerance         ±20%           Voltage - Rated         250V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 85°C           Operating Temperature         -25°C ~ 85°C           Polarization         Polar           Applications         General Purpose           Ripple Current - Low Frequency         3.32A @ 120Hz           Ripple Current - High Frequency         4.98A @ 50kHz           Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)		Aluminum Electrolytic Capacitors
Capacitance1000µFTolerance±20%Voltage - Rated250VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.32A @ 120HzRipple Current - High Frequency4.98A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.378" Dia (35.00mm)Height - Seated (Max)1.260" (32.00mm)	Package	Radial, Can - Snap-In
Tolerance ±20%  Voltage - Rated 250V  ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.32A @ 120Hz  Ripple Current - High Frequency 4.98A @ 50kHz  Impedance - Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)	Series	SMQ
Voltage - Rated 250V  ESR (Equivalent Series Resistance) -  Lifetime @ Temp. 2000 Hrs @ 85°C  Operating Temperature -25°C ~ 85°C  Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.32A @ 120Hz  Ripple Current - High Frequency 4.98A @ 50kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)	Capacitance	1000μF
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Polar  Applications  General Purpose  Ripple Current - Low Frequency  3.32A @ 120Hz  Ripple Current - High Frequency  4.98A @ 50kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)	Tolerance	±20%
Lifetime @ Temp.  2000 Hrs @ 85°C  Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  4.98A @ 50kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)	Voltage - Rated	250V
Operating Temperature  -25°C ~ 85°C  Polarization  Applications  General Purpose  Ripple Current - Low Frequency  Ripple Current - High Frequency  4.98A @ 50kHz  Impedance  -  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)	ESR (Equivalent Series Resistance)	-
Polarization Polar  Applications General Purpose  Ripple Current - Low Frequency 3.32A @ 120Hz  Ripple Current - High Frequency 4.98A @ 50kHz  Impedance -  Lead Spacing 0.394" (10.00mm)  Size / Dimension 1.378" Dia (35.00mm)  Height - Seated (Max) 1.260" (32.00mm)	Lifetime @ Temp.	2000 Hrs @ 85°C
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  4.98A @ 50kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  General Purpose  3.32A @ 120Hz  4.98A @ 50kHz  1.260" (32.00mm)	Operating Temperature	-25°C ~ 85°C
Ripple Current - Low Frequency  Ripple Current - High Frequency  4.98A @ 50kHz  Impedance  Lead Spacing  0.394" (10.00mm)  Size / Dimension  1.378" Dia (35.00mm)  Height - Seated (Max)  1.260" (32.00mm)	Polarization	Polar
Ripple Current - High Frequency       4.98A @ 50kHz         Impedance       -         Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.378" Dia (35.00mm)         Height - Seated (Max)       1.260" (32.00mm)	Applications	General Purpose
Impedance         -           Lead Spacing         0.394" (10.00mm)           Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)	Ripple Current - Low Frequency	3.32A @ 120Hz
Lead Spacing       0.394" (10.00mm)         Size / Dimension       1.378" Dia (35.00mm)         Height - Seated (Max)       1.260" (32.00mm)	Ripple Current - High Frequency	4.98A @ 50kHz
Size / Dimension         1.378" Dia (35.00mm)           Height - Seated (Max)         1.260" (32.00mm)	Impedance	-
Height - Seated (Max) 1.260" (32.00mm)	Lead Spacing	0.394" (10.00mm)
•	Size / Dimension	1.378" Dia (35.00mm)
	Height - Seated (Max)	1.260" (32.00mm)
Surface Mount Land Size -	Surface Mount Land Size	-
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case Radial, Can - Snap-In	Package / Case	Radial, Can - Snap-In
Report errors?		Report errors?

### ESMQ251VSN102MA30S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

#### ESMQ251VSN102MA30S Payment Methods



















#### ESMQ251VSN102MA30S Shipping Methods













If you have any question about ESMQ251VSN102MA30S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com