

ESMQ351VSN821MR50S

ESMQ351VSN821MR50S Information



For Reference Only

Part Number ESMQ351VSN821MR50S

Manufacturer United Chemi-Con

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 820UF 20% 350V SNAP

Package Radial, Can - Snap-In

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESMQ351VSN821MR50S Specifications

| Manufacturer Part Number ESMQ351VSN821MR50S Manufacturer United Chemi-Con Category Capacitors Package Radial, Can - Snap-In Series SMQ Capacitance 820μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization General Purpose Ripple Current - Low Frequency 3,25A @ 120Hz Ripple Current - High Frequency 4,648A @ 50kHz Impedance - Lead Spacing 0,394" (10.00mm) Size / Dimension 1,181" Dia (30.00mm) Height - Seated (Max) 1,969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | <u> </u> | |
|---|------------------------------------|----------------------------------|
| Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - Snap-In Series SMQ Capacitance 820µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing O.394" (10.00mm) Size / Dimension Lieght - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Radial, Can - Snap-In | Manufacturer Part Number | ESMQ351VSN821MR50S |
| Package Radial, Can - Snap-In Series SMQ Capacitance 820µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Manufacturer | United Chemi-Con |
| Package Radial, Can - Snap-In Series SMQ Capacitance 820µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Category | Capacitors |
| Series SMQ Capacitance 820μF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | | Aluminum Electrolytic Capacitors |
| Capacitance 820µF Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Package | Radial, Can - Snap-In |
| Tolerance ±20% Voltage - Rated 350V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Series | SMQ |
| Voltage - Rated350VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 85°COperating Temperature-25°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency3.25A @ 120HzRipple Current - High Frequency4.648A @ 50kHzImpedance-Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Capacitance | 820μF |
| ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Tolerance | ±20% |
| Lifetime @ Temp. Operating Temperature -25°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Voltage - Rated | 350V |
| Operating Temperature -25°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | ESR (Equivalent Series Resistance) | - |
| Polarization Applications General Purpose Ripple Current - Low Frequency 3.25A @ 120Hz Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Lifetime @ Temp. | 2000 Hrs @ 85°C |
| Applications Ripple Current - Low Frequency Ripple Current - High Frequency 4.648A @ 50kHz Impedance Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Operating Temperature | -25°C ~ 85°C |
| Ripple Current - Low Frequency Ripple Current - High Frequency 4.648A @ 50kHz Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Polarization | Polar |
| Ripple Current - High Frequency Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Applications | General Purpose |
| Impedance - Lead Spacing 0.394" (10.00mm) Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Through Hole Package / Case Radial, Can - Snap-In | Ripple Current - Low Frequency | 3.25A @ 120Hz |
| Lead Spacing0.394" (10.00mm)Size / Dimension1.181" Dia (30.00mm)Height - Seated (Max)1.969" (50.00mm)Surface Mount Land Size-Mounting TypeThrough HolePackage / CaseRadial, Can - Snap-In | Ripple Current - High Frequency | 4.648A @ 50kHz |
| Size / Dimension 1.181" Dia (30.00mm) Height - Seated (Max) 1.969" (50.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Impedance | - |
| Height - Seated (Max) Surface Mount Land Size Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Lead Spacing | 0.394" (10.00mm) |
| Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Size / Dimension | 1.181" Dia (30.00mm) |
| Mounting Type Through Hole Package / Case Radial, Can - Snap-In | Height - Seated (Max) | 1.969" (50.00mm) |
| Package / Case Radial, Can - Snap-In | Surface Mount Land Size | - |
| | Mounting Type | Through Hole |
| Report errors? | Package / Case | Radial, Can - Snap-In |
| | | Report errors? |

ESMQ351VSN821MR50S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESMQ351VSN821MR50S Payment Methods



















ESMQ351VSN821MR50S Shipping Methods













If you have any question about ESMQ351VSN821MR50S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com