



ESP050E-1050-42 Information

Heisener.com

Part Number ESP050E-1050-42 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 28-42V 1.05A

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESP050E-1050-42 Specifications

Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Manufacturer Part Number	ESP050E-1050-42	
Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Manufacturer	ERP Power, LLC	
Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Series	ESP	
Number of Outputs 1 Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Type	Constant Current	
Voltage - Input (Min) 220V Voltage - Input (Max) 240V Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Topology	AC DC Converter	
Voltage - Input (Max) Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Size / Dimension 240V 240V 240V 240V 240V 28 ~ 42 V 44W 44W 44W 44W 44W 44W 44W 4	Number of Outputs	1	
Voltage - Output 28 ~ 42 V Current - Output (Max) 1.05A Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Input (Min)	220V	
Current - Output (Max) Power (Watts) 44W Voltage - Isolation Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 1.05A 1.05A	Voltage - Input (Max)	240V	
Power (Watts) 44W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 44W Au Analog, ELV, Triac OCP, OTP, SCP IP64, NEMA 410 -30°C ~ 90°C 87% Wire Leads 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Output	28 ~ 42 V	
Voltage - Isolation	Current - Output (Max)	1.05A	
Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Power (Watts)	44W	
Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Isolation	-	
Ratings IP64, NEMA 410 Operating Temperature $-30^{\circ}\text{C} \sim 90^{\circ}\text{C}$ Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Dimming	Analog, ELV, Triac	
Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Features	OCP, OTP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Ratings	IP64, NEMA 410	
Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Operating Temperature	-30°C ~ 90°C	
Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Efficiency	87%	
` '	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	
			Report errors?

ESP050E-1050-42 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESP050E-1050-42 Payment Methods


































If you have any question about ESP050E-1050-42, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com