

ESP050W-1400-32 Information

Heisener.com

Part Number ESP050W-1400-32 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 21-32V 1.4A

Package

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
Email: salesdant@heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESP050W-1400-32 Specifications

Manufacturer Part Number ESP050W-1400-32 Manufacturer ERP Power, LLC Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 45W Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings 1P64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)		
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Manufacturer Part Number	ESP050W-1400-32
LED Drivers Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Manufacturer	ERP Power, LLC
Package - Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ESP Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)		LED Drivers
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Package	-
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Series	ESP
Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Туре	Constant Current
Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Topology	AC DC Converter
Voltage - Input (Max) 277V Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Number of Outputs	1
Voltage - Output 21 ~ 32 V Current - Output (Max) 1.4A Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Input (Min)	120V
Current - Output (Max) Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 1.4A 45W Analog, ELV, Triac OCP, OTP, SCP 87% Termination Style Wire Leads 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Input (Max)	277V
Power (Watts) 45W Voltage - Isolation - Dimming Analog, ELV, Triac OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 45W Analog, ELV, Triac OCP, OTP, SCP IP64, NEMA 410 -30°C ~ 90°C 87% Wire Leads 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Output	21 ~ 32 V
Voltage - Isolation	Current - Output (Max)	1.4A
Dimming Analog, ELV, Triac Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Power (Watts)	45W
Features OCP, OTP, SCP Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Voltage - Isolation	-
Ratings IP64, NEMA 410 Operating Temperature -30°C ~ 90°C Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Dimming	Analog, ELV, Triac
Operating Temperature $-30^{\circ}\text{C} \sim 90^{\circ}\text{C}$ Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43° L x 2.36° W x 1.07° H $(87.0\text{mm x } 59.9\text{mm x } 27.2\text{mm})$	Features	OCP, OTP, SCP
Efficiency 87% Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Ratings	IP64, NEMA 410
Termination Style Wire Leads Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Operating Temperature	-30°C ~ 90°C
Size / Dimension 3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)	Efficiency	87%
	Termination Style	Wire Leads
Report errors?	Size / Dimension	3.43" L x 2.36" W x 1.07" H (87.0mm x 59.9mm x 27.2mm)
		Report errors?

ESP050W-1400-32 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESP050W-1400-32 Payment Methods



















ESP050W-1400-32 Shipping Methods













If you have any question about ESP050W-1400-32, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com