



ESQ-101-13-S-D-LL Information

Heisener.com

For Reference Only

Part Number ESQ-101-13-S-D-LL

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQ-101-13-S-D-LL Specifications

Manufacturer Part NumberESQ-101-13-S-D-LLManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGold		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Manufacturer Part Number	ESQ-101-13-S-D-LL
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Manufacturer	Samtec Inc.
Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Category	Connectors, Interconnects
Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Package	-
Contact Type Forked Style Board to Board Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Series	ESQ
StyleBoard to BoardNumber of Positions2Number of Positions LoadedAllPitch - Mating-Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-Pull	Connector Type	Elevated Socket
Number of Positions 2 Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Contact Type	Forked
Number of Positions Loaded All Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Style	Board to Board
Pitch - Mating - Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Number of Positions	2
Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-Pull	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-Pull	Pitch - Mating	-
Mounting Type Through Hole Termination Kinked Pin, Solder Fastening Type Push-Pull	Number of Rows	2
Termination Kinked Pin, Solder Fastening Type Push-Pull	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull	Mounting Type	Through Hole
	Termination	Kinked Pin, Solder
Contact Finish - Mating Gold	Fastening Type	Push-Pull
	Contact Finish - Mating	Gold
Contact Finish Thickness - Mating 30µin (0.76µm)	Contact Finish Thickness - Mating	30μin (0.76μm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.435" (11.05mm)	Insulation Height	0.435" (11.05mm)
Contact Length - Post 0.290" (7.37mm)	Contact Length - Post	0.290" (7.37mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQ-101-13-S-D-LL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQ-101-13-S-D-LL Payment Methods



















ESQ-101-13-S-D-LL Shipping Methods













If you have any question about ESQ-101-13-S-D-LL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com