

ESQ-104-34-T-S Information

Heisener.com

For Reference Only

Part Number ESQ-104-34-T-S

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQ-104-34-T-S Specifications

Manufacturer Part Number Manufacturer Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions All Pitch - Mating Number of Rows I Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Insulation Color Black Insulation Height O.280" (7.11mm) Contact Length - Post		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.280" (7.11mm)	Manufacturer Part Number	ESQ-104-34-T-S
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.280" (7.11mm)	Manufacturer	Samtec Inc.
Package - Series ESQ Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Category	Connectors, Interconnects
SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions4Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Package	-
Contact Type Forked Style Board to Board Number of Positions 4 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Series	ESQ
StyleBoard to BoardNumber of Positions4Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)	Connector Type	Elevated Socket
Number of Positions All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Insulation Height Contact Length - Post 0.280" (7.11mm)	Contact Type	Forked
Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)	Number of Positions	4
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlackInsulation Height0.635" (16.13mm)Contact Length - Post0.280" (7.11mm)	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.635" (16.13mm) Contact Length - Post O.280" (7.11mm)	Pitch - Mating	0.100" (2.54mm)
Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Contact Finish - Mating	Tin
Insulation Height 0.635" (16.13mm) Contact Length - Post 0.280" (7.11mm)	Contact Finish Thickness - Mating	-
Contact Length - Post 0.280" (7.11mm)	Insulation Color	Black
-	Insulation Height	0.635" (16.13mm)
0 1 m	Contact Length - Post	0.280" (7.11mm)
Operating Temperature -55°C ~ 105°C	Operating Temperature	-55°C ~ 105°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQ-104-34-T-S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQ-104-34-T-S Payment Methods



















ESQ-104-34-T-S Shipping Methods













If you have any question about ESQ-104-34-T-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com