

# ESQ-106-49-L-S Information

Heisener.com

For Reference Only

Part Number ESQ-106-49-L-S Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ESQ-106-49-L-S Specifications**

Manufacturer Part Number         ESQ-106-49-L-S           Manufacturer         Samtec Inc.           Category         Connectors, Interconnects           Package         -           Series         ESQ           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         ESQ           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	ESQ-106-49-L-S
Package       -         Series       ESQ         Connector Type       Elevated Socket         Contact Type       Forked         Style       Board to Board         Number of Positions       6         Number of Positions Loaded       All         Pitch - Mating       0.100" (2.54mm)         Number of Rows       1         Row Spacing - Mating       -         Mounting Type       Through Hole         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Gold         Contact Finish Thickness - Mating       10µin (0.25µm)         Insulation Color       Black         Insulation Height       0.535" (13.60mm)         Contact Length - Post       0.380" (9.65mm)         Operating Temperature       -55°C ~ 125°C	Manufacturer	Samtec Inc.
Package         -           Series         ESQ           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects
Series         ESQ           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket  Contact Type Forked  Style Board to Board  Number of Positions 6  Number of Positions Loaded All  Pitch - Mating 0.100" (2.54mm)  Number of Rows 1  Row Spacing - Mating -  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 10µin (0.25µm)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.380" (9.65mm)  Operating Temperature - 55°C ~ 125°C	Package	-
Contact Type         Forked           Style         Board to Board           Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C	Series	ESQ
StyleBoard to BoardNumber of Positions6Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions         6           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         1           Row Spacing - Mating         -           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.380" (9.65mm)           Operating Temperature         -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating 0.100" (2.54mm)  Number of Rows 1  Row Spacing - Mating -  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 10µin (0.25µm)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.380" (9.65mm)  Operating Temperature -55°C ~ 125°C	Number of Positions	6
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $10\mu in (0.25\mu m)$ Insulation ColorBlackInsulation Height $0.535" (13.60mm)$ Contact Length - Post $0.380" (9.65mm)$ Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.535$ " $(13.60$ mm)  Contact Length - Post $0.380$ " $(9.65$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Row Spacing - Mating	-
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.535$ " $(13.60$ mm)  Contact Length - Post $0.380$ " $(9.65$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Mounting Type	Through Hole
Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu in (0.25\mu m)$ Insulation Color Black  Insulation Height $0.535" (13.60mm)$ Contact Length - Post $0.380" (9.65mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Termination	Solder
Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.535$ " $(13.60$ mm)  Contact Length - Post $0.380$ " $(9.65$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.535"$ ( $13.60mm$ )Contact Length - Post $0.380"$ ( $9.65mm$ )Operating Temperature $-55$ °C ~ $125$ °C	Contact Finish - Mating	Gold
Insulation Height $0.535" (13.60mm)$ Contact Length - Post $0.380" (9.65mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post $0.380" (9.65 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.535" (13.60mm)
	Contact Length - Post	0.380" (9.65mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### ESQ-106-49-L-S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## ESQ-106-49-L-S Payment Methods



















# ESQ-106-49-L-S Shipping Methods













If you have any question about ESQ-106-49-L-S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com