

ESQ-131-58-S-D-LL

ESQ-131-58-S-D-LL Information

Heisener.com		ESQ-131-58-S-D-LL	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	HIGH SEE
	Description	ELEVATED SOCKET STRIPS	
	Package	-	回診院裁判
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQ-131-58-S-D-LL Specifications

ManufacturerSantec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.100" (2.54mm)Number of Rows2Row Spacing - MatingO.100" (2.54mm)Munting TypeThrough HoleFreminationKinked Pin, SolderFastening TypeOldContact Finish - MatingGoldContact Finish - MatingJojun (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)		
CategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQConnector TypeElevated SocketConnector TypeForkedContact TypeBoard to BoardNumber of Positions62Number of Positions LoadedAllPich - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddGoldGoldContact Finish Thickness - Mating3ujin (0.76µm)Insulation ColorBlackInsulation Height0.535° (13.60mm)Contact Length - Post0.380° (9.65mm)	Manufacturer Part Number	ESQ-131-58-S-D-LL
AckageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows2Row Spacing - Mating0.100° (2.54mm)Mounting TypeDinor (2.54mm)TerminationKinked Pin, SolderFastening TypeOddGotact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.350° (13.60mm)Contact Length - Post0.380° (9.65mm)	Manufacturer	Samtec Inc.
Package-SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening Type9ush-PullContact Finish - MatingGoldContact Finish - MatingSipin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Category	Connectors, Interconnects
SeriesESQConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOddContact Finish - MatingGoldContact Finish Thickness - MatingJuni (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening Type9ush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypeOudContact Finish - MatingGoldContact Finish - MatingBackInsulation ColorBlackInsulation Height0.380" (9.65mm)	Series	ESQ
StyleBoard to BoardNumber of Positions62Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting Type0.100" (2.54mm)TerminationThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Connector Type	Elevated Socket
Number of Positions 62 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 2 Row Spacing - Mating 0.100" (2.54mm) Mounting Type 0.100" (2.54mm) Termination Kinked Pin, Solder Fastening Type Vunber Of Positions Contact Finish - Mating Gold Contact Finish Thickness - Mating Sipin (0.76µm) Insulation Color Black Insulation Height 0.535" (13.60mm) Contact Length - Post 0.380" (9.65mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (0.65mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3/µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Number of Positions	62
Number of Rows2Number of Rows0.100" (2.54mm)Row Spacing - MatingThrough HoleMounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Number of Rows	2
TerminationKinked Pin, SolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Row Spacing - Mating	0.100" (2.54mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Termination	Kinked Pin, Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Contact Finish - Mating	Gold
Insulation Height0.535" (13.60mm)Contact Length - Post0.380" (9.65mm)	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post 0.380" (9.65mm)	Insulation Color	Black
	Insulation Height	0.535" (13.60mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Length - Post	0.380" (9.65mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQ-131-58-S-D-LL Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQ-131-58-S-D-LL Payment Methods



If you have any question about ESQ-131-58-S-D-LL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com