



Heisener.com

For Reference Only

# ESQT-102-02-L-D-610 Information

Part Number ESQT-102-02-L-D-610

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ESQT-102-02-L-D-610 Specifications

Manufacturer Part Number         ESQT-102-02-L-D-610           Manufacturer         Samtec Inc.           Category         Connectors, Interconnects           Package         -           Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         4           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.610" (15.49mm)           Contact Length - Post         0.240" (6.10mm)           Operating Temperature         -55°C ~ 125°C           Material Flammability Rating         UL94 V-0		
Category         Connectors, Interconnects           Package         -           Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         4           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.610" (15.49mm)           Contact Length - Post         0.240" (6.10mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	ESQT-102-02-L-D-610
Package       -         Series       FleXYZ? ESQT         Connector Type       Elevated Socket         Contact Type       Forked         Style       Board to Board or Cable         Number of Positions       4         Number of Positions Loaded       All         Pitch - Mating       0.079" (2.00mm)         Number of Rows       2         Row Spacing - Mating       0.079" (2.00mm)         Mounting Type       Through Hole         Termination       Solder         Fastening Type       Push-Pull         Contact Finish - Mating       Gold         Contact Finish Thickness - Mating       10µin (0.25µm)         Insulation Color       Black         Insulation Height       0.610" (15.49mm)         Contact Length - Post       0.240" (6.10mm)         Operating Temperature       -55°C ~ 125°C	Manufacturer	Samtec Inc.
Package         -           Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         4           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.610" (15.49mm)           Contact Length - Post         0.240" (6.10mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions4Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions4Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         4           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.610" (15.49mm)           Contact Length - Post         0.240" (6.10mm)           Operating Temperature         -55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions4Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions All Pitch - Mating O.079" (2.00mm) Number of Rows 2 Row Spacing - Mating O.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post O.240" (6.10mm) Operating Temperature  4  All All All All All All All All All	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating 0.079" (2.00mm)  Number of Rows 2  Row Spacing - Mating 0.079" (2.00mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 10µin (0.25µm)  Insulation Color Black  Insulation Height 0.610" (15.49mm)  Contact Length - Post 0.240" (6.10mm)  Operating Temperature -55°C ~ 125°C	Number of Positions	4
Number of Rows2Row Spacing - Mating $0.079"$ ( $2.00mm$ )Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $10\mu in (0.25\mu m)$ Insulation ColorBlackInsulation Height $0.610"$ ( $15.49mm$ )Contact Length - Post $0.240"$ ( $6.10mm$ )Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.610" (15.49mm)Contact Length - Post0.240" (6.10mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.610$ " $(15.49$ mm)  Contact Length - Post $0.240$ " $(6.10$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.610$ " $(15.49$ mm)  Contact Length - Post $0.240$ " $(6.10$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Mounting Type	Through Hole
Contact Finish - Mating Gold  Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.610$ " $(15.49$ mm)  Contact Length - Post $0.240$ " $(6.10$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Termination	Solder
Contact Finish Thickness - Mating $10\mu$ in $(0.25\mu$ m)  Insulation Color Black  Insulation Height $0.610$ " $(15.49$ mm)  Contact Length - Post $0.240$ " $(6.10$ mm)  Operating Temperature $-55$ °C $\sim 125$ °C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.610"$ (15.49mm)Contact Length - Post $0.240"$ (6.10mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish - Mating	Gold
Insulation Height $0.610" (15.49 \text{mm})$ Contact Length - Post $0.240" (6.10 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post $0.240" (6.10 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.610" (15.49mm)
	Contact Length - Post	0.240" (6.10mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### ESQT-102-02-L-D-610 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ESQT-102-02-L-D-610 Payment Methods



















### ESQT-102-02-L-D-610 Shipping Methods













If you have any question about ESQT-102-02-L-D-610, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com