



Heisener.com

For Reference Only

ESQT-102-02-S-T-375 Information

Part Number ESQT-102-02-S-T-375

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQT-102-02-S-T-375 Specifications

Manufacturer Part NumberESQT-102-02-S-T-375ManufacturerSamtee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C				
Category Connectors, Interconnects Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 3 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Black Insulation Height 0.375" (9.53mm) Contact Length - Post 0.475" (12.07mm) Operating Temperature -55°C ~ 125°C	Manufacturer Part Number	ESQT-102-02-S-T-375		
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 3 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10.375" (9.53mm) Contact Length - Post 0.475" (12.07mm) Operating Temperature -55°C ~ 125°C	Manufacturer	Samtec Inc.		
Package-SeriesFIEXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects		
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Package	-		
Contact Type Forked Style Board to Board or Cable Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 3 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Black Insulation Height 0.375" (9.53mm) Contact Length - Post 0.475" (12.07mm) Operating Temperature -55°C ~ 125°C	Series	FleXYZ? ESQT		
StyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket		
Number of Positions 6 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 3 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μin (0.76μm) Insulation Color Black Insulation Height 0.375" (9.53mm) Contact Length - Post 0.475" (12.07mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked		
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable		
Pitch - Mating $0.079"$ ($2.00mm$)Number of Rows3Row Spacing - Mating $0.079"$ ($2.00mm$)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $30\mu in (0.76\mu m)$ Insulation ColorBlackInsulation Height $0.375"$ ($9.53mm$)Contact Length - Post $0.475"$ ($12.07mm$)Operating Temperature $-55°C \sim 125°C$	Number of Positions	6		
Number of Rows3Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All		
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.375" (9.53mm)Contact Length - Post0.475" (12.07mm)Operating Temperature-55°C ~ 125°C	Number of Rows	3		
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30 μ in (0.76 μ m) Insulation Color Black Insulation Height 0.375" (9.53mm) Contact Length - Post 0.475" (12.07mm) Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)		
Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30μ in $(0.76\mu$ m) Insulation Color Black Insulation Height 0.375 " $(9.53$ mm) Contact Length - Post 0.475 " $(12.07$ mm) Operating Temperature -55 °C ~ 125 °C	Mounting Type	Through Hole		
Contact Finish - Mating Gold Contact Finish Thickness - Mating $30\mu in (0.76\mu m)$ Insulation Color Black Insulation Height $0.375" (9.53mm)$ Contact Length - Post $0.475" (12.07mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Termination	Solder		
Contact Finish Thickness - Mating 30μ in $(0.76\mu m)$ Insulation Color Black Insulation Height $0.375''$ $(9.53mm)$ Contact Length - Post $0.475''$ $(12.07mm)$ Operating Temperature -55° C $\sim 125^{\circ}$ C	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height $0.375"$ ($9.53mm$)Contact Length - Post $0.475"$ ($12.07mm$)Operating Temperature -55 °C ~ 125 °C	Contact Finish - Mating	Gold		
Insulation Height $0.375" (9.53mm)$ Contact Length - Post $0.475" (12.07mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	30μin (0.76μm)		
Contact Length - Post $0.475''$ (12.07mm) Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black		
Operating Temperature -55°C ~ 125°C	Insulation Height	0.375" (9.53mm)		
	Contact Length - Post	0.475" (12.07mm)		
	Operating Temperature	-55°C ~ 125°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Tin	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?

ESQT-102-02-S-T-375 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-102-02-S-T-375 Payment Methods



















ESQT-102-02-S-T-375 Shipping Methods













If you have any question about ESQT-102-02-S-T-375, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com