

ESQT-103-03-G-D-394

ESQT-103-03-G-D-394 Information

Heisener.com Gistal Write data Terr	Part Number Manufacturer Category Description Package	ESQT-103-03-G-D-394 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS		
For Deferring Only	C	For the pricing/inventory/lead time, please contact		
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-103-03-G-D-394 Specifications

ManufacturerSantec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0:079° (2:00mm)Number of Rows0:079° (2:00mm)Number of Rows0:079° (2:00mm)FerninationSolderForting TypeThrough HoleContact Finish - MatingOidContact Finish - MatingOidInsulation ColorBlackInsulation FlexesJoujin (0.51µm)Insulation Flexes0:04° (1.63mm)			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079"(2.00mm)Number of Rows2Row Spacing - Mating0.079"(2.00mm)Mounting TypeInfough HoleForminationSolderForsteining TypeQuin (0.51µm)Contact Finish - MatingOujon (0.51µm)Insulation ColorBlackInsulation Height0.394"(10.00mm)Contact Length - Post0.064"(1.63mm)	Manufacturer Part Number	ESQT-103-03-G-D-394	
Icctangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFlcXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)YenniationSolderForninationSolderFortart Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Finish0.394" (10.00mm)Contact Finish Posti0.049" (1.63mm)	Manufacturer	Samtec Inc.	
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderFarminationSolderForster InitiationSolderContact Finish - MatingOut (0.51µm)Contact Finish - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Category	Connectors, Interconnects	
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJourn (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Package	-	
Contact TypeForkedStyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOn79" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.394" (1.03mm)Contact Length - Post0.064" (1.63mm)	Series	FleXYZ? ESQT	
StyleBoard to Board or CableNumber of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Connector Type	Elevated Socket	
Number of Positions6Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Contact Type	Forked	
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Style	Board to Board or Cable	
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2/uin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Number of Positions	6	
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Number of Positions Loaded	All	
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Pitch - Mating	0.079" (2.00mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Row Spacing - Mating	0.079" (2.00mm)	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Termination	Solder	
Contact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Contact Finish - Mating	Gold	
Insulation Height0.394" (10.00mm)Contact Length - Post0.064" (1.63mm)	Contact Finish Thickness - Mating	20µin (0.51µm)	
Contact Length - Post 0.064" (1.63mm)	Insulation Color	Black	
	Insulation Height	0.394" (10.00mm)	
Operating Temperature -55° C $\sim 125^{\circ}$ C	Contact Length - Post	0.064" (1.63mm)	
	Operating Temperature	-55°C ~ 125°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-103-03-G-D-394 Payment Methods



If you have any question about ESQT-103-03-G-D-394, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com