

Heisener.com

For Reference Only

ESQT-106-02-L-D-604 Information

Part Number ESQT-106-02-L-D-604

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQT-106-02-L-D-604 Specifications

Manufacturer Part Number Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Contact Finish - Mating 10µin (0.25µm) Insulation Color Black Insulation Height		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Manufacturer Part Number	ESQT-106-02-L-D-604
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Manufacturer	Samtec Inc.
Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black	Package	-
Contact Type Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black	Series	FleXYZ? ESQT
Style Board to Board or Cable Number of Positions 12 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black	Connector Type	Elevated Socket
Number of Positions12Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Number of Positions	12
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Row Spacing - Mating	0.079" (2.00mm)
Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Mounting Type	Through Hole
Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Termination	Solder
Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	10μin (0.25μm)
Insulation Unicht 0.604" (15.25mm)	Insulation Color	Black
insulation Height 0.004 (13.33min)	Insulation Height	0.604" (15.35mm)
Contact Length - Post 0.246" (6.25mm)	Contact Length - Post	0.246" (6.25mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-106-02-L-D-604 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-106-02-L-D-604 Payment Methods



















ESQT-106-02-L-D-604 Shipping Methods













If you have any question about ESQT-106-02-L-D-604, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com