

# ESQT-110-02-L-6-450

## ESQT-110-02-L-6-450 Information

Heisener.com	Part Number	ESQT-110-02-L-6-450	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	122.0.02
	Package	-	回認提業的
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# ESQT-110-02-L-6-450 Specifications

ManufacturerSamee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketConnector TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPich - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQoldContact Finish - MatingGoldContact Finish - MatingJuin (0.25µm)Insulation ColorBlack		
CategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedSoriesSoried to Board or CableNumber of Positions60Number of Positions LoadedAllPich - Mating0.079" (2.0mm)Number of Rows6Number of Rows0.079" (2.0mm)Number of Rows0.079" (2.0mm)Number of Rows6.014Nourting TypeNongh HolePicninationSolderFerninationSolderContact Finish - MatingGoldContact Finish - MatingInjui (0.25µm)Insulation ColorBlack	Manufacturer Part Number	ESQT-110-02-L-6-450
IdentifyRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Numing TypeSolderPatenting TypeSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBack	Manufacturer	Samtec Inc.
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOsdContact Finish - MatingGoldContact Finish - MatingBiack	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish - MatingBiak		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.019Insulation ColorBlack	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeDifferentiationFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldIontact Finish Thickness - MatingBlack	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIontact Finish Thickness - MatingIoµin (0.25µm)Insulation ColorBlack	Connector Type	Elevated Socket
Number of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldNotat Finish Thickness - MatingInjun (0.25µm)Insulation ColorBlack	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlack	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Number of Positions	60
Number of Rows6Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Number of Rows	6
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack	Termination	Solder
Contact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	10μin (0.25μm)
Insulation Height 0.450" (11.43mm)	Insulation Color	Black
	Insulation Height	0.450" (11.43mm)
Contact Length - Post 0.400" (10.16mm)	Contact Length - Post	0.400" (10.16mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

### ESQT-110-02-L-6-450 Guarantees



#### **Quality Guarantees**


We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# ESQT-110-02-L-6-450 Payment Methods



If you have any question about ESQT-110-02-L-6-450, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com