



Heisener.com

For Reference Only

# ESQT-110-02-L-D-374 Information

Part Number ESQT-110-02-L-D-374

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ESQT-110-02-L-D-374 Specifications

Manufacturer Part NumberESQT-110-02-L-D-374ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)Operating Temperature-55°C ~ 125°C		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets  Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 20 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.476" (12.09mm) Contact Length - Post	Manufacturer Part Number	ESQT-110-02-L-D-374
Package         -           Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.374" (9.50mm)           Contact Length - Post         0.476" (12.09mm)	Manufacturer	Samtec Inc.
Package         -           Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10µin (0.25µm)           Insulation Color         Black           Insulation Height         0.374" (9.50mm)           Contact Length - Post         0.476" (12.09mm)	Category	Connectors, Interconnects
Series         FleXYZ? ESQT           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board or Cable           Number of Positions         20           Number of Positions Loaded         All           Pitch - Mating         0.079" (2.00mm)           Number of Rows         2           Row Spacing - Mating         0.079" (2.00mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         10μin (0.25μm)           Insulation Color         Black           Insulation Height         0.374" (9.50mm)           Contact Length - Post         0.476" (12.09mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions20Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Connector Type	Elevated Socket
Number of Positions  Number of Positions Loaded  All  Pitch - Mating  0.079" (2.00mm)  Number of Rows  2  Row Spacing - Mating  0.079" (2.00mm)  Mounting Type  Through Hole  Termination  Solder  Fastening Type  Push-Pull  Contact Finish - Mating  Gold  Contact Finish Thickness - Mating  Insulation Color  Black  Insulation Height  0.374" (9.50mm)  Contact Length - Post  0.476" (12.09mm)	Contact Type	Forked
Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.374" (9.50mm) Contact Length - Post 0.476" (12.09mm)	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Number of Positions	20
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Number of Rows	2
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.374" (9.50mm) Contact Length - Post 0.476" (12.09mm)	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.374" (9.50mm)Contact Length - Post0.476" (12.09mm)	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black Insulation Height 0.374" (9.50mm) Contact Length - Post 0.476" (12.09mm)	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.374" (9.50mm) Contact Length - Post 0.476" (12.09mm)	Contact Finish - Mating	Gold
Insulation Height 0.374" (9.50mm)  Contact Length - Post 0.476" (12.09mm)	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post 0.476" (12.09mm)	Insulation Color	Black
	Insulation Height	0.374" (9.50mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Length - Post	0.476" (12.09mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

# ESQT-110-02-L-D-374 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ESQT-110-02-L-D-374 Payment Methods



















### ESQT-110-02-L-D-374 Shipping Methods













If you have any question about ESQT-110-02-L-D-374, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com