

ESQT-110-03-M-Q-335

ESQT-110-03-M-Q-335 Information

Heisener.com	Part Number Manufacturer	ESQT-110-03-M-Q-335 Samtec Inc	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	2861822
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-110-03-M-Q-335 Specifications

Manufacturer Part NumberESQT-110-03-M-Q-335ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnactor TypeElevated SocketContact TypeSoard to Board or CableNumber of Positions40Number of Positions LoadedAllNumber of Rows4Rew Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuid (0.51µm)Contact Finish - Mating0.010 (51µm)Contact Finish - MatingGoldContact Finish - MatingGoldContact Finish - Mating0.010 (51µm)Contact Finish - Mating0.010 (51µm)Contact Finish - Mating0.010 (51µm)Contact Finish Thickness - Mating0.33" (8.51nm)Contact Finish Thickness - Mating0.123" (3.12nm)Operating Temperature-55°C ~ 125°CMaterial Flammability RatingUL94 V-0		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllNumber of Rows4Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Number of RowsSolderNounting TypeNongh HoleSteining TypeSolderContact Finish - MatingOidContact Finish - MatingGoldInsulation ColorBlackInsulation Flexing0.035" (8.51mm)Contact Length - Post0.123" (3.12mm)Contact Length - Post0.55° C + 125°C	Manufacturer Part Number	ESQT-110-03-M-Q-335
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingGoldContact Finish Thickness - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFlcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeDioderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.51µm)Insulation ColorBlackInsulation Height0.33" (8.51nm)Contact Length - Post.123" (3.12mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening Type9uh-PuhlContact Finish - MatingGoldContact Finish - Mating2uju (0.51µm)Insulation ColorBlackInsulation Height0.33" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingOidInsulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.019" (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating0.019" (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post50°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 40 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Juni (0.51µm) Insulation Color Black Insulation Height 0.335" (8.51mm) Contact Length - Post 0.123" (3.12mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Number of Positions	40
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.335" (8.51mm)Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.335" (8.51mm) Contact Length - Post 0.123" (3.12mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post0.123" (3.12mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.335" (8.51mm)
	Contact Length - Post	0.123" (3.12mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-110-03-M-Q-335 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-110-03-M-Q-335 Payment Methods



If you have any question about ESQT-110-03-M-Q-335, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com