



ESQT-112-02-F-5-703 Information

Heisener.com

For Reference Only

Part Number ESQT-112-02-F-5-703

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQT-112-02-F-5-703 Specifications

| Manufacturer Part Number ESQT-112-02-F-5-703 Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 5 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Juin (0.08µm) Insulation Color Black Insulation Height 0.703" (17.86mm) Contact Length - Post 0.147" (3.73mm) Operating Temperature -55°C ~ 125°C Material Flammability Rating UL94 V-0 | | |
|--|-----------------------------------|---|
| Category Connectors, Interconnects Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 5 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3µin (0.08µm) Insulation Color Black Insulation Height 0.703" (17.86mm) Contact Length - Post 0.147" (3.73mm) Operating Temperature -55°C ~ 125°C | Manufacturer Part Number | ESQT-112-02-F-5-703 |
| Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Manufacturer | Samtec Inc. |
| Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 5 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3µin (0.08µm) Insulation Color Black Insulation Height 0.703" (17.86mm) Contact Length - Post 0.147" (3.73mm) Operating Temperature -55°C ~ 125°C | Category | Connectors, Interconnects |
| SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 5 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3µin (0.08µm) Insulation Color Black Insulation Height 0.703" (17.86mm) Contact Length - Post 0.147" (3.73mm) Operating Temperature -55°C ~ 125°C | Package | - |
| Contact Type Forked Style Board to Board or Cable Number of Positions 60 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 5 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3μin (0.08μm) Insulation Color Black Insulation Height 0.703" (17.86mm) Contact Length - Post 0.147" (3.73mm) Operating Temperature -55°C ~ 125°C | Series | FleXYZ? ESQT |
| StyleBoard to Board or CableNumber of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Connector Type | Elevated Socket |
| Number of Positions60Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Contact Type | Forked |
| Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Style | Board to Board or Cable |
| Pitch - Mating0.079" (2.00mm)Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Number of Positions | 60 |
| Number of Rows5Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Number of Positions Loaded | All |
| Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Pitch - Mating | 0.079" (2.00mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.703" (17.86mm)Contact Length - Post0.147" (3.73mm)Operating Temperature-55°C ~ 125°C | Number of Rows | 5 |
| Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3μ in $(0.08\mu$ m) Insulation Color Black Insulation Height $0.703''$ $(17.86$ mm) Contact Length - Post $0.147''$ $(3.73$ mm) Operating Temperature -55° C $\sim 125^{\circ}$ C | Row Spacing - Mating | 0.079" (2.00mm) |
| Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 3μ in $(0.08\mu$ m) Insulation Color Black Insulation Height 0.703 " $(17.86$ mm) Contact Length - Post 0.147 " $(3.73$ mm) Operating Temperature -55 °C ~ 125 °C | Mounting Type | Through Hole |
| Contact Finish - Mating Gold Contact Finish Thickness - Mating 3μ in $(0.08\mu m)$ Insulation Color Black Insulation Height $0.703''$ $(17.86mm)$ Contact Length - Post $0.147''$ $(3.73mm)$ Operating Temperature -55° C $\sim 125^{\circ}$ C | Termination | Solder |
| Contact Finish Thickness - Mating 3μ in $(0.08\mu m)$ Insulation Color Black Insulation Height $0.703''$ $(17.86mm)$ Contact Length - Post $0.147''$ $(3.73mm)$ Operating Temperature -55° C $\sim 125^{\circ}$ C | Fastening Type | Push-Pull |
| Insulation ColorBlackInsulation Height $0.703"$ (17.86mm)Contact Length - Post $0.147"$ (3.73mm)Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Contact Finish - Mating | Gold |
| Insulation Height $0.703" (17.86mm)$ Contact Length - Post $0.147" (3.73mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Contact Finish Thickness - Mating | 3μin (0.08μm) |
| Contact Length - Post $0.147" (3.73mm)$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Insulation Color | Black |
| Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$ | Insulation Height | 0.703" (17.86mm) |
| | Contact Length - Post | 0.147" (3.73mm) |
| Material Flammability Rating UL94 V-0 | Operating Temperature | -55°C ~ 125°C |
| | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |

ESQT-112-02-F-5-703 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-112-02-F-5-703 Payment Methods



















ESQT-112-02-F-5-703 Shipping Methods













If you have any question about ESQT-112-02-F-5-703, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com