

# ESQT-112-03-L-Q-360

## ESQT-112-03-L-Q-360 Information

Heisener.com	Part Number Manufacturer Category Description Package	ESQT-112-03-L-Q-360 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## ESQT-112-03-L-Q-360 Specifications

ManufacturerSantec Inc.CategoryConnectors, InterconnectsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Mounting TypeThrough HoleStyleSolderRow Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleContact Finish - MatingSolderRoute I StyleBoard to EstenceNumber of Rows4Row Spacing - MatingSolderTerminationSolderFastening TypeUsh-PullContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeSordetContact TypeBoard to Board or CableNumber of Positions48Number of Positions LoadedAllNumber of Rows4Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Number of RowsSolderNounting TypeSolderFreminationSolderContact Finish - MatingOidContact Finish - MatingIopin (0.25µm)Insulation ColorBlackInsulation FlexesJouin (0.25µm)Insulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Contact Funst, Thickness - MatingSolderInsulation FlexesSolderSolder SolderSolderSolder Sol	Manufacturer Part Number	ESQT-112-03-L-Q-360
Image: Part of the sector of	Manufacturer	Samtec Inc.
Package-SeriesFlcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllNumber of Rows4Row Spacing - Mating0.079" (2.00mm)Number of Rows0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeVanhPullContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.360" (2.00mm)Foratel Length - Post0.098" (2.50mm)Contact Finish Thickness - Mating0.360" (2.41mm)Contact Finish Thickness - Mating0.360" (2.41mm)Contact Finish Thickness - Mating0.360" (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Length - Post0.958" (2.50mm)Contact Length - Post0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Length - Post0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Length - Post0.958" (2.50mm)Contact Finish Thickness0.958" (2.50mm)Contact Length - Post0.958"	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOddContact Finish - MatingGoldContact Finish - MatingIpin (0.25µm)Insulation ColorBlackInsulation Height0.360" (2.00mm)Contact Length - Post0.098" (2.50mm)Contact Finish Thickness - MatingSider (2.50mm)Contact Finish Thickness - MatingSider (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Finish ThicknesSider (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Finish FinishSider (2.50mm)Contact Finish ThicknesSider (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Length - PostSider (2.50mm)Contact Finish ThicknesSider		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.360" (2.50mm)Contact Length - Post0.998" (2.50mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.010Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 48   Number of Positions Loaded All   Pitch - Mating 0.079" (2.00mm)   Number of Rows 4   Row Spacing - Mating 0.079" (2.00mm)   Mounting Type 0.079" (2.00mm)   Termination 0.079" (2.00mm)   Termination Solder   Fastening Type Push-Pull   Contact Finish - Mating Gold   Contact Finish Thickness - Mating Jupin (0.25µm)   Insulation Color Black   Insulation Height 0.060" (9.14mm)   Contact Length - Post 0.098" (2.50mm)   Operating Temperature -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions	48
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.360" (9.14mm)   Contact Length - Post 0.098" (2.50mm)   Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.360" (9.14mm)
	Contact Length - Post	0.098" (2.50mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### ESQT-112-03-L-Q-360 Guarantees



#### **Quality Guarantees**


We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# ESQT-112-03-L-Q-360 Payment Methods



If you have any question about ESQT-112-03-L-Q-360, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com