

ESQT-112-03-M-D-310

ESQT-112-03-M-D-310 Information

Heisener.com	Part Number Manufacturer Category Description Package	ESQT-112-03-M-D-310 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets CONN SOCKET 2MM 24POS DUAL ROW	
For Reference Only		For the pricing/inventory/lead time, please contact us	
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-112-03-M-D-310 Specifications

Manufacturer Part NumberESQT-112-03-M-D-310ManufacturerSamee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTContact TypeElevated SocketContact TypeBoard or CableStyleBoard or CableNumber of Positions24Number of Positions Loaded1079° (200mm)Number of Rows2Row Spacing - Mating0,079° (200mm)Munting TypeSolderTerminationSolderStreing TypeGold Osard or CableStreing TypeGolderStreing TypeGolderStreing TypeSolderStreing TypeSolderStreing TypeGoldor SolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSoldor SolderStreing TypeSolderStreing TypeSoldor SolderStreing TypeSoldor SolderStreing TypeSoldor SolderStreing TypeSoldor SolderStreing TypeSoldor SolderStreing TypeSolderStreing TypeSoldor SolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSolderStreing TypeSolder <t< th=""><th></th><th></th></t<>		
CategoryConnectors. InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllNumber of Rows2Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of RowsSolderStore TypeMinoga HoleNumber of Rows0.019° (2.00mm)Number of Rows	Manufacturer Part Number	ESQT-112-03-M-D-310
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingGoldContact Finish Thickness - MatingQuin (0.51µm)Sulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFicXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Contact Fungt - Post55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Fungh-Post55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeUsh-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - Mating0.010" (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingOuj (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.310" (7.87mm) Contact Length - Post 0.146" (3.70mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature55°C ~ 125°C	Number of Positions	24
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.310" (7.87mm)Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.310" (7.87mm) Contact Length - Post 0.146" (3.70mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post0.146" (3.70mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.310" (7.87mm)
	Contact Length - Post	0.146" (3.70mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-112-03-M-D-310 Payment Methods



If you have any question about ESQT-112-03-M-D-310, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com