

ESQT-113-02-G-S-750

ESQT-113-02-G-S-750 Information

Heisener.com	Part Number	ESQT-113-02-G-S-750	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	日本が後日
	Description	ELEVATED 2MM SOCKETS	3 5576,552
	Package	-	- 国際授業的
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-113-02-G-S-750 Specifications

ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllNumber of Rows1Number of Rows1Number of RowsSolderNumber of RowsSolderString TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackInsulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)				
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXY2? ESQT Connector Type Elevated Socket Connector Type Forked Connector Type Board to Board or Cable Style Board to Board or Cable Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Quin (0.51µm) Contact Finish - Mating Old Contact Finish Thickness - Mating Juin (0.51µm) Insulation Color Black Insulation Height 0.750" (19.05mm) Contact Length - Post 0.100" (2.54mm)	Manufacturer Part Number	ESQT-113-02-G-S-750		
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeQuán (0.51µm)Contact Finish - MatingOjon (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Manufacturer	Samtec Inc.		
Package-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Category	Connectors, Interconnects		
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFerninationSolderFastening TypeOddContact Finish - MatingGoldContact Finish Thickness - MatingOjun (0.51µm)Insulation ColorBlackInsulation Height0.70" (2.54µm)		Rectangular Connectors - Headers, Receptacles, Female Sockets		
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypeOutpleContact Finish - MatingGoldContact Finish - MatingBiakInsulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Package	-		
Contact TypeForkedStyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFortninationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Series	FleXYZ? ESQT		
StyleBoard to Board or CableNumber of Positions13Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Connector Type	Elevated Socket		
Number of Positions 13 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Isulation Color Black Insulation Height 0.750" (19.05mm) Contact Length - Post 0.100" (2.54mm)	Contact Type	Forked		
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting Type-TerminationSolderFastening TypePush-PullContact Finish - MatingOjui (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Style	Board to Board or Cable		
Pitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting Type-TerminationSolderFastening TypePush-PullContact Finish - MatingOdi (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Number of Positions	13		
Number of Rows1Number of Rows-Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Number of Positions Loaded	All		
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Pitch - Mating	0.079" (2.00mm)		
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Number of Rows	1		
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Row Spacing - Mating	-		
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Mounting Type	Through Hole		
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Termination	Solder		
Contact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Fastening Type	Push-Pull		
Insulation ColorBlackInsulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Contact Finish - Mating	Gold		
Insulation Height0.750" (19.05mm)Contact Length - Post0.100" (2.54mm)	Contact Finish Thickness - Mating	20µin (0.51µm)		
Contact Length - Post 0.100" (2.54mm)	Insulation Color	Black		
	Insulation Height	0.750" (19.05mm)		
0 (; T (; 10500	Contact Length - Post	0.100" (2.54mm)		
Operating Temperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C		
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0		

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-113-02-G-S-750 Payment Methods



If you have any question about ESQT-113-02-G-S-750, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com