

ESQT-115-03-M-D-360

ESQT-115-03-M-D-360 Information

Heisener.com	Part Number Manufacturer Category Description Package	ESQT-115-03-M-D-360 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
For Reference Only		For the pricing/inventory/lead time, please contact us	EIF578.0+4
Torreference only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-115-03-M-D-360 Specifications

Manufacturer Part NumberESQT-115-03-M-D-360ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTContact TypeElevated SocketContact TypeBoard or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypeOush-PullContact Finish - Mating0.019" (2.00mm)Contact Finish - MatingSolderTerminationSolderFastening TypeOush-PullContact Finish - Mating0.030" (0.51µm)Contact Finish - Mating0.060" (0.51µm)Contact Finish Thickness - Mating0.360" (0.14mm)Contact Length - Post0.98" (2.50mm)Operating Temperature-55" C~ 125" CMaterial Flammability RatingUL94 V-0		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Board to Board or Cable Style Board to Board or Cable Number of Positions 30 Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Youngh Type Solder Youngh Type Solder<	Manufacturer Part Number	ESQT-115-03-M-D-360
Indext of the sector of the	Manufacturer	Samtec Inc.
Package-SeriesFicXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeVanhPullContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBackInsulation Finish - Mating3.06" (1.41mm)Contact Finish Thickness - Mating0.360" (9.14mm)Insulation Finish - Mating0.360" (9.14mm)Contact Finish Thickness - Mating0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Length - Post0.998" (2.50mm)Contact Finish Thotact55" C~ 125" C	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeTorough HoleTerminationSolderFastening TypeOddContact Finish - MatingGoldContact Finish - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.360" (2.50mm)Contact Length - Post0.998" (2.50mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (.00mm)Number of Rows2Row Spacing - Mating0.079" (.00mm)Mounting TypeDiorg (.00mm)ForminationSolderForminationSolderContact Finish - MatingOidInsulation ColorBlackInsulation Height0.360" (1.4mm)Contact Length - Post0.98" (2.50mm)Contact Funish - Mating0.98" (2.50mm)Insulation Height0.98" (2.50mm)Contact Length - Post0.98" (2.50mm)Contact Length - Post0.98" (2.50mm)Contact Funish - Post0.98" (2.50mm)Contact Funish - Post0.98" (2.50mm)Contact Length - Post0.98" (2.50mm)Contact Funish - Post0.98" (2.50mm)Contact Funi	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.019" (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14µm)Contact Length - Post0.98" (2.50mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions30Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOn79" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingOujni (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 30 Number of Positions Loaded All Number of Positions Loaded 0.079" (2.00mm) Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.360" (9.14mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions	30
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.360" (9.14mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.360" (9.14mm)Contact Length - Post0.098" (2.50mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.360" (9.14mm) Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post 0.098" (2.50mm) Operating Temperature -55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.360" (9.14mm)
	Contact Length - Post	0.098" (2.50mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESQT-115-03-M-D-360, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com