

ESQT-117-03-M-D-338

ESQT-117-03-M-D-338 Information

	Part Number Manufacturer Category	Connectors, Interconnects	
Codditioner auforter	Description	Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
	Package	-	回認授業的
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-117-03-M-D-338 Specifications

Manufacturer Part NumberESQT-117-03-M-D-338ManufacturerSamtee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTContact TypeElevated SocketContact TypeBoard or CableStyleBoard or CableNumber of Positions34Number of Positions Loaded1079° (2.00mm)Number of Rows2Row Spacing - MatingJolf? (2.00mm)Munting TypeSolderFreminationSolderStreing TypeGold (5.1µm)Contact Finish - MatingSolderContact Finish - MatingSolderStreing TypeGold (5.1µm)Streing TypeSolderStreing TypeSolderContact Finish - MatingSolderContact Finish - MatingSolderStreing TypeSolderStreing TypeSolderContact Finish - MatingSolderContact Finish - MatingSolderStreing TypeSolderStreing TypeSolder<		
CategoryConnectors. InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079° (2.00mm)Number of Rows2Row Spacing - MatingSolderMounting TypeThrough HoleFreminationSolderContact Finish - MatingOidContact Finish - MatingOidu (0.51µm)Insulation ColorBlackInsulation FlexesJasi (8.59mm)Contact Length - Post0.120° (3.05mm)Contact Length - PostSick - 25°C	Manufacturer Part Number	ESQT-117-03-M-D-338
Package.SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingQuin (0.51µm)Contact Finish Thickness - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (2.05°C	Manufacturer	Samtec Inc.
Package-SeriesFeXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish - MatingOidContact Finish Thickness - MatingJakInsulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllNumber of Rows2Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Number of Rows0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.33" (8.59mm)Contact Length - Post0.120" (3.05mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - Mating0.0ju (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions34Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJouin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Contact Fungerature55°C ~ 125°C	Number of Positions	34
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2/µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height0.338" (8.59mm)Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post0.120" (3.05mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.338" (8.59mm)
	Contact Length - Post	0.120" (3.05mm)
Material Flammability Rating UL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

VISA

ESQT-117-03-M-D-338 Payment Methods

ESQT-117-03-M-D-338 Shipping Methods



If you have any question about ESQT-117-03-M-D-338, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com