

ESQT-119-02-F-Q-510

ESQT-119-02-F-Q-510 Information

Heisener.com	Part Number	ESQT-119-02-F-Q-510	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	日前後期日 2、25歳年のにす 第日に来る。
	Description Package	ELEVATED 2MM SOCKETS -	- 25日末秋公 - 国际教授来社
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-119-02-F-Q-510 Specifications

ManufacturerSamtec Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating50derFortured TypeSolderFastening TypeOldContact Finish - MatingSolderSolderSolderFastening TypeBush-PullContact Finish - MatingGoldSolderSolderFastening TypeSolderInsulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature55°C ~ 125°C		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllNumber of Rows4Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of RowsSolderNouning TypeSolderFreminationSolderContact Finish - MatingGoldContact Finish - MatingGoldSulation ColorBackInsulation ColorBackInsulation Flexit0.510° (12.95mm)Contact Length - Post0.340° (8.64mm)Operating Temperature0.55° C 125°C	Manufacturer Part Number	ESQT-119-02-F-Q-510
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeOnder HoleTerminationSolderFastening TypeOusf NotaleGoldGuldContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFlcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeDioderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOudOntact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact Type Forked Style Board to Board or Cable Number of Positions 76 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.510" (12.95mm) Contact Length - Post 0.340" (8.64mm) Operating Temperature -55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions76Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Number of Positions	76
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJain (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64µm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJini (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.510" (12.95mm)Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.510" (12.95mm) Contact Length - Post 0.340" (8.64mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	3μin (0.08μm)
Contact Length - Post0.340" (8.64mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.510" (12.95mm)
	Contact Length - Post	0.340" (8.64mm)
Material Flammability Rating UI.94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-119-02-F-Q-510 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-119-02-F-Q-510 Payment Methods



If you have any question about ESQT-119-02-F-Q-510, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com