

ESQT-120-02-M-D-700

ESQT-120-02-M-D-700 Information

Heisener.com	Part Number Manufacturer Category Description	ESQT-120-02-M-D-700 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
	Package	-	「同時時期」
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-120-02-M-D-700 Specifications

Manufacturer Part NumberESQT-120-02-M-D-700ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard or CableNumber of Positions40Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuin (0.51µm)Contact Finish Thickness - MatingQuin (0.51µm)Insulation ColorBlackInsulation Flexifielt0.700" (1.78mm)Contact Length - Post0.150" (3.81 mm)Operating Temmerature0.5°C ~ 125°CMaterial Flammability RatingU194 V-0		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Board to Board or Cable Style Board to Board or Cable Number of Positions 40 Number of Positions Loaded All Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Youngh Hole Solder Termination Solder Contact Finish - Mating Oujui (0.51µm) Contact Finish Thickness - Mating Quipu (0.51µm) Insulation Color Black Insulation Height 0.700" (17.78mm) Sortact Length - Post 0.150" (3.81mm)	Manufacturer Part Number	ESQT-120-02-M-D-700
Indext of the sector of the	Manufacturer	Samtec Inc.
Package-SeriesFicXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPich - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)Your Spacing - Mating0.079" (2.00mm)Your Spacing - Mating0.079" (2.00mm)Your Spacing - MatingSolderYour Spacing - MatingSolderYour Spacing - MatingSolderYour Spacing - MatingGoldYour Spacing - MatingSolderYour Spacing - Mating - MatingSolderYour Spacing - Mating - Matin	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOntog (1.00mm)FartninationSolderForstening TypeOidContact Finish - MatingGoldContact Finish - MatingQuin (0.51µm)Insulation ColorBlackInsulation Height0.700" (1.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (.00mm)Number of Rows2Row Spacing - Mating0.079" (.00mm)Mounting TypeDiorg (.00mm)FarminationSolderForminationSolderContact Finish - MatingOidIonator Finish - MatingOidIonator ColorBlackInsulation Color0.70" (1.78mm)Ionator Height0.50" c~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.010" (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions40Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 40 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.700" (17.78mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Number of Positions	40
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.700" (17.78mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.700" (17.78mm)Contact Length - Post0.150" (3.81mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.700" (17.78mm) Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post 0.150" (3.81mm) Operating Temperature -55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.700" (17.78mm)
	Contact Length - Post	0.150" (3.81mm)
Material Flammability Rating UI.94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESQT-120-02-M-D-700, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com