

ESQT-121-02-F-D-760

ESQT-121-02-F-D-760 Information

| | Part Number Manufacturer | ESQT-121-02-F-D-760 Samtec Inc. | |
|--------------------|-----------------------------|----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------|
| Heisener.com | Category | Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets | 10000000000000000000000000000000000000 |
| | Description | ELEVATED 2MM SOCKETS | 77.78.82 |
| | Package | - | 「同説授業は |
| For Reference Only | | For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-121-02-F-D-760 Specifications

| ManufacturerSamtec Inc.CategoryConnectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPick - Mating0.079° (2.00mm)Number of Rows2Row Spacing - Mating0.079° (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuidContact Finish - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingJii (0.08µm)Insulation ColorBlackInsulation Height0.70° (2.29mm)Contact Length - Post0.090° (2.29mm)Operating Temperature-55°C ~ 125°C | | |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------|---------------------------------------------------------------|
| CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? EQTConnector TypeElevated SocketContact TypeForkedContact TypeBoard to Board or CableNumber of Positions42Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of RowsSolderForninationSolderForninationSolderContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.760° (19.30mm)Contact Length - Post0.090° (2.29mm)Contact Length - Post0.50° C 125°C | Manufacturer Part Number | ESQT-121-02-F-D-760 |
| Image: Part of the sector of | Manufacturer | Samtec Inc. |
| Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.909" (2.29µm)Operating Temperature55°C ~ 125°C | Category | Connectors, Interconnects |
| SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.760" (12.9mm)Operating Temperature-55°C ~ 125°C | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.90" (2.29mm)Operating Temperature-55°C ~ 125°C | Package | - |
| Contact Type Forked Style Board to Board or Cable Number of Positions 42 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.760" (19.30mm) Contact Funsh - Post 0.900" (2.29mm) | Series | FleXYZ? ESQT |
| StyleBoard to Board or CableNumber of Positions42Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post50°C ~ 125°C | Connector Type | Elevated Socket |
| Number of Positions 42 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Juin (0.08µm) Insulation Color Black Insulation Height 0.760" (19.30mm) Contact Length - Post 0.090" (2.29mm) | Contact Type | Forked |
| Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature55°C ~ 125°C | Style | Board to Board or Cable |
| Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiakInsulation ColorJane (19.30mm)Insulation Height0.760" (19.30mm)Contact Length - Post55°C ~ 125°C | Number of Positions | 42 |
| Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Number of Positions Loaded | All |
| Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJini (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.900" (2.29mm)Operating Temperature-55°C ~ 125°C | Pitch - Mating | 0.079" (2.00mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Number of Rows | 2 |
| TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Row Spacing - Mating | 0.079" (2.00mm) |
| Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Mounting Type | Through Hole |
| Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Termination | Solder |
| Contact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Fastening Type | Push-Pull |
| Insulation ColorBlackInsulation Height0.760" (19.30mm)Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Contact Finish - Mating | Gold |
| Insulation Height 0.760" (19.30mm) Contact Length - Post 0.090" (2.29mm) Operating Temperature -55°C ~ 125°C | Contact Finish Thickness - Mating | 3µin (0.08µm) |
| Contact Length - Post0.090" (2.29mm)Operating Temperature-55°C ~ 125°C | Insulation Color | Black |
| Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ | Insulation Height | 0.760" (19.30mm) |
| | Contact Length - Post | 0.090" (2.29mm) |
| Material Flammability Rating UL94 V-0 | Operating Temperature | -55°C ~ 125°C |
| | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |

ESQT-121-02-F-D-760 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

VISA

ESQT-121-02-F-D-760 Payment Methods

ESQT-121-02-F-D-760 Shipping Methods



If you have any question about ESQT-121-02-F-D-760, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com