



Heisener.com

For Reference Only

ESQT-124-02-GF-S-787 Information

Part Number ESQT-124-02-GF-S-787

Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED 2MM SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESQT-124-02-GF-S-787 Specifications

Manufacturer Part Number ESQT-124-02-GF-S-787 Manufacturer Samtee Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm) Operating Temperature -55°C ~ 125°C		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height Contact Length - Post 0.063" (1.60mm)	Manufacturer Part Number	ESQT-124-02-GF-S-787
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Manufacturer	Samtec Inc.
Package - Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Category	Connectors, Interconnects
Series FleXYZ? ESQT Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Forked Style Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Package	-
Contact Type Forked Style Board to Board or Cable Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions24Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Connector Type	Elevated Socket
Number of Positions 24 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Contact Type	Forked
Number of Positions Loaded Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.787" (19.99mm) Contact Length - Post O.063" (1.60mm)	Style	Board to Board or Cable
Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Number of Positions	24
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Number of Positions Loaded	All
Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.787" (19.99mm)Contact Length - Post0.063" (1.60mm)	Termination	Solder
Contact Finish Thickness - Mating 20μin (0.51μm) Insulation Color Black Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Contact Finish - Mating	Gold
Insulation Height 0.787" (19.99mm) Contact Length - Post 0.063" (1.60mm)	Contact Finish Thickness - Mating	20μin (0.51μm)
Contact Length - Post 0.063" (1.60mm)	Insulation Color	Black
•	Insulation Height	0.787" (19.99mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Length - Post	0.063" (1.60mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-124-02-GF-S-787 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-124-02-GF-S-787 Payment Methods



















ESQT-124-02-GF-S-787 Shipping Methods













If you have any question about ESQT-124-02-GF-S-787, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com