

ESQT-124-02-L-D-309

ESQT-124-02-L-D-309 Information

(A Heisener.com	Part Number Manufacturer Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles,	
	Description	Female Sockets ELEVATED 2MM SOCKETS	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-124-02-L-D-309 Specifications

Manufacturer Part NumberESQT-124-02-L-D-309ManufacturerSamtec Inc.CategoryConnectors, InterconnectsPackage-Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions Loaded0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFreminationSolderFastening TypeQuid AllContact Finish - MatingGoldContact Finish Thickness - MatingIopin (0.25µm)		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of PositionsAllNumber of Positions Loaded0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeSolderForminationSolderFastening TypeGudGotact Finish - MatingGod	Manufacturer Part Number	ESQT-124-02-L-D-309
AckageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeGold	Manufacturer	Samtec Inc.
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedO.079" (2.00mm)Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingO.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOsh-PullContact Finish - MatingGold	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - Mating0.079° (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeGold		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuest Public AutometerFontact Finish - MatingGold	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeGoldGontact Finish - MatingGold	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGold	Connector Type	Elevated Socket
Number of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGold	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Positions	48
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGold	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGold	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGold	Mounting Type	Through Hole
Contact Finish - Mating Gold	Termination	Solder
	Fastening Type	Push-Pull
Contact Finish Thickness - Mating 10µin (0.25µm)	Contact Finish - Mating	Gold
	Contact Finish Thickness - Mating	10μin (0.25μm)
Insulation Color Black	Insulation Color	Black
Insulation Height 0.309" (7.85mm)	Insulation Height	0.309" (7.85mm)
Contact Length - Post 0.541" (13.74mm)	Contact Length - Post	0.541" (13.74mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-124-02-L-D-309 Payment Methods



If you have any question about ESQT-124-02-L-D-309, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com