

ESQT-124-03-S-D-320

ESQT-124-03-S-D-320 Information

Heisener.com		ESQT-124-03-S-D-320	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	9004980 900498703 900498703
	Description	ELEVATED 2MM SOCKETS	515TR/ 452
	Package	-	回冷漠般
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-124-03-S-D-320 Specifications

Manufacturer Part NumberESQT-124-03-S-D-320ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard or CableNumber of PositionsAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish - Mating0.30" (8.13mm)Contact Length - Post0.138" (3.50mm)Contact Length - Post0.138" (3.50mm)Contact Length - Post0.126" (2.1000000000000000000000000000000000000		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeSord to Board or CableNumber of Positions48Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079° (2.00mn)Number of Rows0.079° (2.00mn)Number of Rows3.01FreminationSolderFortand TypeMachael SocketContact Finish - MatingOidContact Finish - MatingGoldContact Finish Thickness - MatingJojin (0.76µm)Insulation CloorBlackInsulation Height0.320° (8.13mn)Contact Length - Post0.138° (3.50mn)Contact Finish ThicknesSolderInsulation Height0.320° (8.13mn)Contact Length - PostSolderContact Finish ThicknesSolderSolder SolderSolderSolder Solder		
Indext of the sector of the	Manufacturer	Samtec Inc.
Package-SeriesFIcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeVush-PullContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Contact Finish Thota55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOntog HoleFreminationSolderForstening TypeOldContact Finish - MatingGoldContact Finish - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.0176µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions48Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 48 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 30µin (0.76µm) Insulation Color Black Insulation Height 0.320" (8.13mm) Contact Length - Post 0.138" (3.50mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions	48
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.320" (8.13mm)Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.320" (8.13mm) Contact Length - Post 0.138" (3.50mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)
Contact Length - Post0.138" (3.50mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.320" (8.13mm)
	Contact Length - Post	0.138" (3.50mm)
Material Elementative Dating	Operating Temperature	-55°C ~ 125°C
Material Flammaonity Kating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-124-03-S-D-320 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-124-03-S-D-320 Payment Methods WIRE transfer PayPal Methods ESQT-124-03-S-D-320 Shipping Methods Fedex. I Control Total Interval I

If you have any question about ESQT-124-03-S-D-320, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com