

ESQT-125-03-L-D-372

ESQT-125-03-L-D-372 Information

Heisener.com	Part Number	ESQT-125-03-L-D-372	
	Manufacturer		
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	1.5.10.22
	Package	-	回診時業に
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-125-03-L-D-372 Specifications

Manufacturer Part NumberESQ1-125-03-12ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketConnector TypeForkedStyleBoard or CableNumber of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - Mating0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)Operating Temperature-55°C ~ 125°C		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeInfough HoleForninationSolderFortart Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Manufacturer Part Number	ESQT-125-03-L-D-372
Icetanguar Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFacX72 RSQTConnector TypeElevated SocketContact TypeForedStyleBoard to Board or CableNumber of PositionsSolNumber of Positions LoadedAllPich - Mating0.079° (2.00mm)Number of Rows2Rowspacing - Mating0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.019° (2.00mm) <td< td=""><td>Manufacturer</td><td>Samtec Inc.</td></td<>	Manufacturer	Samtec Inc.
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of PositionsS0Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingNorghe HoleMounting TypeSolderFarminationSolderFortact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingIpin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOldContact Finish - MatingGoldContact Finish Thickness - MatingIlpuin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOn79" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Connector Type	Elevated Socket
Number of Positions50Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Number of Positions	50
Number of Rows2Number of Rows0.079" (2.00mm)Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Termination	Solder
Contact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Contact Finish - Mating	Gold
Insulation Height0.372" (9.44mm)Contact Length - Post0.086" (2.18mm)	Contact Finish Thickness - Mating	10µin (0.25µm)
Contact Length - Post 0.086" (2.18mm)	Insulation Color	Black
-	Insulation Height	0.372" (9.44mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Length - Post	0.086" (2.18mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-125-03-L-D-372 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-125-03-L-D-372 Payment Methods



If you have any question about ESQT-125-03-L-D-372, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com