

ESQT-126-03-F-Q-365

ESQT-126-03-F-Q-365 Information

Heisener.com	Part Number	ESQT-126-03-F-Q-365	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	1.212.24
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-126-03-F-Q-365 Specifications

Manufacturer Part NumberESQT-126-03-F-Q-365ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Finish - MatingSolderFastening TypeBoard to Board or CableFinish - MatingSolderFinish - MatingSolderFastening TypeBoard to SolderFastening TypeSolderFastening TypeSolderFinish - MatingSolderContact Finish - MatingSolderContact Finish - MatingSolderFusilation ColorBlackInsulation ColorSolderFinish Thickness - MatingSolderFinish Finish Fi		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketConnector TypeElevated SocketContact TypeBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPich - Mating0.079° (2.00mm)Number of Rows4Row Spacing - Mating0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.019° (2.00mm)FreinnationSolderForninationSolderForninationGoldContact Finish - MatingGoldContact Finish - MatingBiakInsulation ColorBiaksInsulation Height0.35° (9.27mm)	Manufacturer Part Number	ESQT-126-03-F-Q-365
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Manufacturer	Samtec Inc.
Package-SeriesFleXYZ? ESQTConactor TypeElevated SocketConact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.365" (9.27mm)	Category	Connectors, Interconnects
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.365" (9.27mm)	Connector Type	Elevated Socket
Number of Positions104Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.355" (9.27mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJini (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Number of Positions	104
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleMounting TypeSolderTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Termination	Solder
Contact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.365" (9.27mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.365" (9.27mm)	Contact Finish - Mating	Gold
Insulation Height 0.365" (9.27mm)	Contact Finish Thickness - Mating	3µin (0.08µm)
	Insulation Color	Black
	Insulation Height	0.365" (9.27mm)
Contact Length - Post 0.093" (2.35mm)	Contact Length - Post	0.093" (2.35mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-126-03-F-Q-365 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

VISA

ESQT-126-03-F-Q-365 Payment Methods

ESQT-126-03-F-Q-365 Shipping Methods



If you have any question about ESQT-126-03-F-Q-365, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com