

ESQT-127-03-H-S-309

ESQT-127-03-H-S-309 Information

	Part Number Manufacturer	ESQT-127-03-H-S-309 Samtec Inc		
Contact in the second s	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets		
	Description	ELEVATED 2MM SOCKETS		
	Package	-	目記法教徒	
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote	

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-127-03-H-S-309 Specifications

Manufacturer Part NumberESQT-127-03-H-S-309ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketConnector TypeSorde To Board or CableStyleBoard or CableNumber of Positions LoadedAllNumber of Rows1Number of Rows1Number of RowsSolderNumber of RowsSolderStyleSolderNumber of Rows1StyleSolderNumber of RowsSolderNumber of RowsSolderStyleS			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeSord to Board or CableStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllNumber of Rows1Number of Rows0.079° (2.00mm)Number of Rows1Number of Rows5.0derNumber of Rows0.019° (2.00mm)Number of Rows1Number of Rows1Number of Rows0.019° (2.00mm)Number of Rows0.019° (2	Manufacturer Part Number	ESQT-127-03-H-S-309	
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeBoard to Board or CableStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.	
Package-SeriesFIcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPich - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeodelYourge TypeSolderFreminationSolderFortact Finish - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingJoin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Fungh - Post0.149" (3.78mm)Contact Finish Post55°C ~ 125°C	Category	Connectors, Interconnects	
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeSolderFareninationSolderForster InstriktSolderContact Finish - MatingGoldContact Finish - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.309° (7.85mm)Contact Length - Post0.149° (3.78mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.019" (2.00µm)Insulation ColorBlackInsulation Height0.309" (7.85µm)Contact Length - Post0.149" (3.78µm)Operating Temperature-55°C ~ 125°C	Package	-	
Contact TypeForkedStyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT	
StyleBoard to Board or CableNumber of Positions27Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket	
Number of Positions 27 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Jouin (0.76µm) Insulation Color Black Insulation Height 0.309" (7.85mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked	
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature55°C ~ 125°C	Style	Board to Board or Cable	
Pitch - Mating0.079" (2.00mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Contact Fungerature55°C ~ 125°C	Number of Positions	27	
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJupin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All	
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Number of Rows	1	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	-	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull	
Insulation ColorBlackInsulation Height0.309" (7.85mm)Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold	
Insulation Height 0.309" (7.85mm) Contact Length - Post 0.149" (3.78mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
Contact Length - Post0.149" (3.78mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.309" (7.85mm)	
	Contact Length - Post	0.149" (3.78mm)	
Material Flammability Pating III 04 V 0	Operating Temperature	-55°C ~ 125°C	
Utatenai Planinaointy Kating 01.94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-127-03-H-S-309 Payment Methods



If you have any question about ESQT-127-03-H-S-309, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com