

ESQT-128-02-G-D-590

ESQT-128-02-G-D-590 Information

Heisener.com	Part Number Manufacturer Category Description	ESQT-128-02-G-D-590 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
	Package	-	回認證辨論
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	Request a Quote
		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-128-02-G-D-590 Specifications

ManufacturerSame c Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketConnector TypeForkedContact TypeBoard to Board or CableStyleSocketNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - MatingNorge (2.00mm)Mounting TypeInfough HoleForminationSolderFastening TypeOsldContact Finish - MatingGoldContact Finish - MatingSolderInsulation ColorBlack			
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions66Number of Positions Loaded1079° (2.0mm)Number of Rows2Number of Rows0.079° (2.0mm)Number of Rows0.079° (2.0mm)Number of Rows0.079° (2.0mm)Number of Rows0.079° (2.0mm)Number of Rows0.019° (2.0mm)Number of Rows	Manufacturer Part Number	ESQT-128-02-G-D-590	
HeckageRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - Mating0.079° (2.00mm)Mounting TypeHoley HoleyFarminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldIsulation ColorBack	Manufacturer	Samtec Inc.	
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOsdContact Finish - MatingGoldContact Finish - MatingBoard or CableIsulation ColorBlack	Category	Connectors, Interconnects	
SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - MatingGoldInsulation ColorBlack		Rectangular Connectors - Headers, Receptacles, Female Sockets	
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeOndContact Finish - MatingOidInsulation ColorBlack	Package	-	
Contact TypeForkedStyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type50/derFastening TypeSolderFastening TypeOutputContact Finish - MatingGoldContact Finish Thickness - MatingBlack	Series	FleXYZ? ESQT	
StyleBoard to Board or CableNumber of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldKontact Finish - MatingBiak	Connector Type	Elevated Socket	
Number of Positions56Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.51µm)Insulation ColorBlack	Contact Type	Forked	
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlack	Style	Board to Board or Cable	
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating0.0151 µm)Insulation ColorBlack	Number of Positions	56	
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Number of Positions Loaded	All	
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Pitch - Mating	0.079" (2.00mm)	
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Number of Rows	2	
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Row Spacing - Mating	0.079" (2.00mm)	
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Mounting Type	Through Hole	
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlack	Termination	Solder	
Contact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlack	Fastening Type	Push-Pull	
Insulation Color Black	Contact Finish - Mating	Gold	
	Contact Finish Thickness - Mating	20µin (0.51µm)	
Insulation Height 0.590" (14.99mm)	Insulation Color	Black	
	Insulation Height	0.590" (14.99mm)	
Contact Length - Post 0.260" (6.60mm)	Contact Length - Post	0.260" (6.60mm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C	
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0	

Contact Finish - Post	Gold	
Mated Stacking Heights	-	
Ingress Protection	-	
Features	-	
		Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESQT-128-02-G-D-590, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com