

ESQT-129-02-F-D-770

ESQT-129-02-F-D-770 Information

Heisener.com	Part Number Manufacturer Category	Connectors, Interconnects	
	Description	Rectangular Connectors - Headers, Receptacles, Female Sockets ELEVATED 2MM SOCKETS	
	Package	-	回透暖景
For Reference Only		For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-129-02-F-D-770 Specifications

Manufacturer Part NumberESQT-129-02-F-D-770ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeBoard or CableStyleBoard or CableNumber of PositionsSaNumber of Positions LoadedAllNumber of Rows2Row Spacing - MatingSolderMounting TypeThrough HoleFortact Finish - MatingSolderContact Finish - MatingGoldContact Finish Thickness - MatingGoldSulation ColorBackInsulation ColorBackInsulation ColorJackMating HeightOr70° (2.00mm)Contact Engish - MatingGoldContact Finish Thickness - MatingGoldInsulation ColorBackInsulation Height0.70° (2.03mm)Contact Length - PostJis0° (2.03mm)Contact Ementative RatingJis0° (2.03mm)Contact Length - PostJis0° (2.03mm)Contact Length - PostUI 94 V-0		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeSord to Board or CableStyleBoard to Board or CableNumber of Positions58Number of Positions LoadedAllNumber of Rows2Row Spacing - Mating0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows3Pict - Mating0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.019° (2.00mm)Number of Rows0.010Number of Rows0	Manufacturer Part Number	ESQT-129-02-F-D-770
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeBoard to Board or CableNumber of Positions58Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - MatingJiin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Contact Length - Post0.080" (2.03mm)Contact Finish Thicknes55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFIcXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of PositionsS8Number of Positions LoadedAllPitch - Mating0.079° (2.00mm)Number of Rows2Row Spacing - Mating0.079° (2.00mm)Mounting Type0.079° (2.00mm)Young TypeSolderForninationSolderForting TypeOsderContact Finish - MatingGoldContact Finish Thickness - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.70° (1.95mm)Contact Length - Post0.080° (2.03mm)Soler Contact Finish ThicknessSolderSolder Contact Finish TypeSolderSolder Contact Finish Thickness - MatingSolderSolder Contact Finish ThicknessSolderSolder Contact Finish	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of PositionsS8Number of Positions LoadedAllPitch - Mating0/079" (2.00mm)Number of Rows2Row Spacing - MatingNorgy" (2.00mm)Mounting TypeOid79" (2.00mm)TerminationSolderFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.808" (2.03mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions58Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.70" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions58Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.800" (2.03mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions58Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOn79" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJini (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 58 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 2 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Juin (0.08µm) Insulation Color Black Insulation Height 0.770" (19.56mm) Contact Length - Post 0.080" (2.03mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation Color0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Contact Length - Post55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBiackInsulation Color0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Contact Fungerature55°C ~ 125°C	Number of Positions	58
Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.70" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.770" (19.56mm)Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.770" (19.56mm) Contact Length - Post 0.080" (2.03mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	3µin (0.08µm)
Contact Length - Post0.080" (2.03mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.770" (19.56mm)
	Contact Length - Post	0.080" (2.03mm)
Material Flammability Rating UII 94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESQT-129-02-F-D-770, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com