

ESQT-130-02-M-Q-500

ESQT-130-02-M-Q-500 Information

	Part Number	ESQT-130-02-M-Q-500	
	Manufacturer	Samtec Inc.	
Heisener.com	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	
	Package	-	
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-130-02-M-Q-500 Specifications

Manufacturer Part NumberESQT-130-02-M-Q-500ManufacturerSamtee Inc.CategoryConnectors, InterconnectsPackage-SeriesFleXY2 ESQTConnector TypeElevated SocketConnector TypeElevated SocketContact TypeBardo Board or CableNumber of Positions20Number of Positions LoadedAllPick - Mating0.079" (2.00mm)Number of Rows4Row Spacing - MatingSolderTerminationSolderFastening TypePush-PullContact Finish - Mating20uin (0.51µm)Soltact Finish Thickness - Mating0.030" (12.70mm)Insulation ColorBlackInsulation Finish Thickness - Mating0.030" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature0.55°C ~ 125°CMaterial Elammability BatingII.94 Vo		
CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeSord or CableNumber of Positions10Number of Positions LoadedAllNumber of Rows4Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of Rows0.079° (2.00mm)Number of RowsSolderForeninationSolderForeninationSolderContact Finish - MatingOudOutact Finish - MatingOujn (0.51µm)Insulation ColorBlackInsulation Height0.500° (12.70mn)Contact Finish - MatingSolor (12.70mn)Insulation Height0.500° (12.70mn)Contact Finish Thickness - MatingSolor (12.70mn)Contact Finish Thicknes - MatingSolor (12.70mn)Contact Finish ThicknesSolor (12.70mn) <tr< td=""><td>Manufacturer Part Number</td><td>ESQT-130-02-M-Q-500</td></tr<>	Manufacturer Part Number	ESQT-130-02-M-Q-500
HeadersRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions120Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating0.090" (12.70mm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package-SeriesFlcXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions120Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypeUsh-PullContact Finish - MatingGoldContact Finish - MatingOjo" (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature55°C ~ 125°C	Category	Connectors, Interconnects
SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions120Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeOnfor "Colomm)FerminationSolderFortact Finish - MatingOidContact Finish - MatingGoldContact Finish - MatingOid 0.011m)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions120Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOutputContact Finish - MatingOutputInsulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions120Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating0.01Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Series	FleXYZ? ESQT
Style Board to Board or Cable Number of Positions 120 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Mounting Type Number of Rows Farmination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.500" (12.70mm) Operating Temperature -55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions 120 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Termination 0.079" (2.00mm) Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 20µin (0.51µm) Insulation Color Black Insulation Height 0.500" (12.70mm) Contact Length - Post 0.350" (8.89mm) Operating Temperature -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJuin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingBlackInsulation Color0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature55°C ~ 125°C	Number of Positions	120
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating2/µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.500" (12.70mm)Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Insulation Height 0.500" (12.70mm) Contact Length - Post 0.350" (8.89mm) Operating Temperature -55°C ~ 125°C	Contact Finish Thickness - Mating	20µin (0.51µm)
Contact Length - Post0.350" (8.89mm)Operating Temperature-55°C ~ 125°C	Insulation Color	Black
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Insulation Height	0.500" (12.70mm)
	Contact Length - Post	0.350" (8.89mm)
Material Flammability Rating UIL94 V-0	Operating Temperature	-55°C ~ 125°C
	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESQT-130-02-M-Q-500, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com