

ESQT-146-03-L-D-390

ESQT-146-03-L-D-390 Information

| | | ESQT-146-03-L-D-390 | |
|--------------------|--------------|---|-----------------|
| | Manufacturer | Samtec Inc. | |
| Heisener.com | Category | Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets | |
| | Description | ELEVATED 2MM SOCKETS | |
| | Package | - | |
| For Reference Only | | For the pricing/inventory/lead time, please contact us | |
| | | Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-146-03-L-D-390 Specifications

| ManufacturerSame Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXY2? ESQTConnector TypeElevated SocketConnector TypeElevated SocketContact TypeSoriedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPich - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleForninationSolderFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingBiaka | | |
|--|-----------------------------------|---|
| CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketConnector TypeForkedSoriesBoard to Board or CableStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPich - Mating0.079° (2.00mn)Number of Rows2Rows Pacing - MatingSolderMounting TypeSolderForminationSolderForninationGoldContact Finish - MatingGoldContact Finish - MatingInjun (2.5µm)Insulation ColorBlack | Manufacturer Part Number | ESQT-146-03-L-D-390 |
| Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFarminationSolderFastening TypeUsh-PullContact Finish - MatingGoldInsulation ColorBlack | Manufacturer | Samtec Inc. |
| Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQuid CallContact Finish - MatingGoldContact Finish - MatingBoard to CallInsulation ColorBlack | Category | Connectors, Interconnects |
| SeriesFleXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldIontact Finish - MatingBack | | Rectangular Connectors - Headers, Receptacles, Female Sockets |
| Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - Mating0.012 juni (0.25 juni)Insulation ColorBlack | Package | - |
| Contact TypeForkedStyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeQualContact Finish - MatingGoldContact Finish Thickness - MatingBlack | Series | FleXYZ? ESQT |
| StyleBoard to Board or CableNumber of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIonat Finish Thickness - MatingIupin (0.25µm)BackBlack | Connector Type | Elevated Socket |
| Number of Positions92Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeOn79" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIontact Finish Thickness - MatingIoµin (0.25µm)Insulation ColorBlack | Contact Type | Forked |
| Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingIupin (0.25µm)Insulation ColorBlack | Style | Board to Board or Cable |
| Pitch - Mating0.079" (2.00mm)Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldIontact Finish Thickness - MatingIoµin (0.25µm)Insulation ColorBlack | Number of Positions | 92 |
| Number of Rows2Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Number of Positions Loaded | All |
| Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Pitch - Mating | 0.079" (2.00mm) |
| Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Number of Rows | 2 |
| TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Row Spacing - Mating | 0.079" (2.00mm) |
| Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Mounting Type | Through Hole |
| Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Insulation ColorBlack | Termination | Solder |
| Contact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlack | Fastening Type | Push-Pull |
| Insulation Color Black | Contact Finish - Mating | Gold |
| | Contact Finish Thickness - Mating | 10μin (0.25μm) |
| Insulation Height 0.390" (9.91mm) | Insulation Color | Black |
| 0.570 (7.71111) | Insulation Height | 0.390" (9.91mm) |
| Contact Length - Post 0.068" (1.73mm) | Contact Length - Post | 0.068" (1.73mm) |
| Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$ | Operating Temperature | -55°C ~ 125°C |
| Material Flammability Rating UL94 V-0 | Material Flammability Rating | UL94 V-0 |

| Contact Finish - Post | Tin |
|------------------------|----------------|
| Mated Stacking Heights | - |
| Ingress Protection | - |
| Features | - |
| | Report errors? |





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-146-03-L-D-390 Payment Methods



If you have any question about ESQT-146-03-L-D-390, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com