

ESQT-150-03-F-Q-315

ESQT-150-03-F-Q-315 Information

Heisener.com	Part Number Manufacturer Category	ESQT-150-03-F-Q-315 Samtec Inc. Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED 2MM SOCKETS	1. Sec. 19
	Package	-	回深这类
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESQT-150-03-F-Q-315 Specifications

Manufacturer Part NumberESQT-150-03-F-Q-315ManufacturerSamtec Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeSord to Board or CableNumber of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - MatingSolderPatenting TypeDordy HoleContact Finish - MatingSolderContact Finish - MatingGoldContact Finish - MatingGoldContact Finish - MatingSolderForking SolderJain (0.08µm)Forking SolderSolderForking SolderSolderForking SolderSolderForking SolderSolderContact Finish - MatingGoldContact Finish Thickness - MatingJain (0.08µm)Insulation ColorBlackInsulation Fleph0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)Operating Temperature-55°C ~ 125°C		
CategoryConnectors, InterconnectsCategoryConnectors - Headers, Receptacles, Female SocketsPackage-SeriesFleXYZ? ESQTConnector TypeElevated SocketConnector TypeSocketContact TypeSocketStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOldContact Finish - MatingGoldContact Finish - MatingGoldStation ColorBlackInsulation ColorBlackInsulation Height0.143" (3.63mm)	Manufacturer Part Number	ESQT-150-03-F-Q-315
Actangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesFlcXY2? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeDiolerTerminationSolderFastening TypeOidContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBackInsulation FlostiJins" (8.00mm)Contact Length - Post0.143" (3.63mm)	Manufacturer	Samtec Inc.
Package-SeriesFleXYZ? ESQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOush PublicContact Finish - MatingGoldContact Finish - MatingJin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Category	Connectors, Interconnects
SeriesFleXY2? EQTConnector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypeOldContact Finish - MatingGoldContact Finish Thickness - MatingSin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Package	-
Contact TypeForkedStyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJini (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Series	FleXYZ? ESQT
StyleBoard to Board or CableNumber of Positions200Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Connector Type	Elevated Socket
Number of Positions 200 Number of Positions Loaded All Pitch - Mating 0.079" (2.00mm) Number of Rows 4 Row Spacing - Mating 0.079" (2.00mm) Mounting Type 0.079" (2.00mm) Mounting Type Olorgy" (2.00mm) Termination Solder Fastening Type Solder Contact Finish - Mating Gold Insulation Color Black Insulation Height 0.315" (8.00mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Style	Board to Board or Cable
Pitch - Mating0.079" (2.00mm)Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting Type0.079" (2.00mm)TerminationThrough HoleFastening TypeSolderFontact Finish - MatingOodContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Number of Positions	200
Number of Rows4Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Number of Positions Loaded	All
Row Spacing - Mating0.079" (2.00mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Pitch - Mating	0.079" (2.00mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Number of Rows	4
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Row Spacing - Mating	0.079" (2.00mm)
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - MatingJµin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating3µin (0.08µm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Termination	Solder
Contact Finish Thickness - Mating3μin (0.08μm)Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Contact Finish - Mating	Gold
Insulation Height0.315" (8.00mm)Contact Length - Post0.143" (3.63mm)	Contact Finish Thickness - Mating	3μin (0.08μm)
Contact Length - Post 0.143" (3.63mm)	Insulation Color	Black
	Insulation Height	0.315" (8.00mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Length - Post	0.143" (3.63mm)
	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESQT-150-03-F-Q-315 Guarantees



Quality Guarantees


We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ESQT-150-03-F-Q-315 Payment Methods



If you have any question about ESQT-150-03-F-Q-315, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com