



ESR03EZPJ434 Information



For Reference Only

Part Number ESR03EZPJ434

Manufacturer Rohm Semiconductor

Category Resistors

Chip Resistor - Surface Mount

Description RES SMD 430K OHM 5% 1/4W 0603

Package 0603 (1608 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESR03EZPJ434 Specifications

Manufacturer ESR03EZPJ434 Manufacturer Rohm Semiconductor Category Resistors Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series ESR Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm) Height Sexted (Merc) 0.020" (0.55 mm)			
Category Resistors Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series ESR Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Manufacturer Part Number	ESR03EZPJ434	
Chip Resistor - Surface Mount Package 0603 (1608 Metric) Series ESR Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Manufacturer	Rohm Semiconductor	
Package 0603 (1608 Metric) Series ESR Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Category	Resistors	
Series ESR Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)		Chip Resistor - Surface Mount	
Resistance 430 kOhms Tolerance ±5% Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Package	0603 (1608 Metric)	
Tolerance $\pm 5\%$ Power (Watts) 0.25W, 1/4W Composition Thick Film Features Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient $\pm 200 \text{ppm}/^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Series	ESR	
Power (Watts) 0.25W, 1/4W Composition Thick Film Automotive AEC-Q200, Pulse Withstanding Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Resistance	430 kOhms	
$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	Tolerance	±5%	
Features Automotive AEC-Q200, Pulse Withstanding ±200ppm/°C Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension O.063" L x 0.031" W (1.60mm x 0.80mm)	Power (Watts)	0.25W, 1/4W	
Temperature Coefficient $\pm 200 \text{ppm/}^{\circ}\text{C}$ Operating Temperature $-55^{\circ}\text{C} \sim 155^{\circ}\text{C}$ Package / Case $0603 \ (1608 \ \text{Metric})$ Supplier Device Package 0603 Size / Dimension $0.063^{\circ}\text{L} \times 0.031^{\circ}\text{W} \ (1.60 \text{mm} \times 0.80 \text{mm})$	Composition	Thick Film	
Operating Temperature -55°C ~ 155°C Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Features	Automotive AEC-Q200, Pulse Withstanding	
Package / Case 0603 (1608 Metric) Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Temperature Coefficient	±200ppm/°C	
Supplier Device Package 0603 Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Operating Temperature	-55°C ~ 155°C	
Size / Dimension 0.063" L x 0.031" W (1.60mm x 0.80mm)	Package / Case	0603 (1608 Metric)	
	Supplier Device Package	0603	
Height Sected (May)	Size / Dimension	0.063" L x 0.031" W (1.60mm x 0.80mm)	
rieigiii - Seated (Max) 0.022 (0.55mm)	Height - Seated (Max)	0.022" (0.55mm)	
Number of Terminations 2	Number of Terminations	2	
Failure Rate -	Failure Rate	-	
Report errors's		Report error	s?

ESR03EZPJ434 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESR03EZPJ434 Payment Methods



















ESR03EZPJ434 Shipping Methods













If you have any question about ESR03EZPJ434, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com