

ESS-110-T-08 Information

Heisener.com

For Reference Only

Part Number ESS-110-T-08
Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESS-110-T-08 Specifications

Manufacturer Part Number ESS-110-T-08 Manufacturer Samtec Inc. Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Tennenture 0.365" (9.27mm) Contact Length - Post 0.365" (9.27mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating Insulation Color Black Insulation Height O.300" (7.62mm) Contact Length - Post O.365" (9.27mm)	Manufacturer Part Number	ESS-110-T-08
Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Manufacturer	Samtec Inc.
Package - Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Category	Connectors, Interconnects
Series Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Series	ESS
Style Board to Board Number of Positions 10 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10µin (0.25µm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Connector Type	Elevated Socket
Number of Positions10Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Contact Type	Female Socket
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Number of Positions	10
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Gold Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating10μin (0.25μm)Insulation ColorBlackInsulation Height0.300" (7.62mm)Contact Length - Post0.365" (9.27mm)	Termination	Solder
Contact Finish Thickness - Mating 10μin (0.25μm) Insulation Color Black Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Fastening Type	Push-Pull
Insulation Color Insulation Height O.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Contact Finish - Mating	Gold
Insulation Height 0.300" (7.62mm) Contact Length - Post 0.365" (9.27mm)	Contact Finish Thickness - Mating	10μin (0.25μm)
Contact Length - Post 0.365" (9.27mm)	Insulation Color	Black
	Insulation Height	0.300" (7.62mm)
One area time. To make a real time.	Contact Length - Post	0.365" (9.27mm)
Operating reinperature -55°C ~ 125°C	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESS-110-T-08 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESS-110-T-08 Payment Methods



















ESS-110-T-08 Shipping Methods













If you have any question about ESS-110-T-08, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com