

ESS-111-TT-25 Information

Heisener.com

For Reference Only

Part Number ESS-111-TT-25
Manufacturer Samtec Inc.

Category Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

Description ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESS-111-TT-25 Specifications

Manufacturer Part Number Manufacturer Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions I1 Number of Positions Loaded Pitch - Mating Number of Rows I Row Spacing - Mating Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Insulation Color Black Insulation Height Some Connectors - Headers, Receptacles, Female Sockets Rectangular Connectors - Headers, Receptacles, Female Sockets Package		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black	Manufacturer Part Number	ESS-111-TT-25
Rectangular Connectors - Headers, Receptacles, Female Sockets Package Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating Mounting Type Through Hole Termination Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black	Manufacturer	Samtec Inc.
Package - Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Category	Connectors, Interconnects
Series ESS Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector Type Elevated Socket Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Package	-
Contact Type Female Socket Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Series	ESS
Style Board to Board Number of Positions 11 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating Insulation Color Black	Connector Type	Elevated Socket
Number of Positions	Contact Type	Female Socket
Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Style	Board to Board
Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Number of Positions	11
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingTinContact Finish Thickness - Mating-Insulation ColorBlack	Number of Positions Loaded	All
Row Spacing - Mating Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black	Pitch - Mating	0.100" (2.54mm)
Mounting Type Through Hole Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Number of Rows	1
Termination Solder Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Row Spacing - Mating	-
Fastening Type Push-Pull Contact Finish - Mating Tin Contact Finish Thickness - Mating - Insulation Color Black	Mounting Type	Through Hole
Contact Finish - Mating Contact Finish Thickness - Mating Insulation Color Black	Termination	Solder
Contact Finish Thickness - Mating Insulation Color Black	Fastening Type	Push-Pull
Insulation Color Black	Contact Finish - Mating	Tin
	Contact Finish Thickness - Mating	-
Insulation Height 0.500" (12.70mm)	Insulation Color	Black
· · · · · ·	Insulation Height	0.500" (12.70mm)
Contact Length - Post 0.173" (4.40mm)	Contact Length - Post	0.173" (4.40mm)
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

ESS-111-TT-25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESS-111-TT-25 Payment Methods



















ESS-111-TT-25 Shipping Methods













If you have any question about ESS-111-TT-25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com