

### ESS015E-0350-42 Information



For Reference Only

Part Number ESS015E-0350-42 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

**LED Drivers** 

**Description** LED DRIVER CC AC/DC 28-42V 350MA

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ESS015E-0350-42 Specifications

Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         ESS           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Input (Max)         240V           Voltage - Output         28 ~ 42 V           Current - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)			
Category         Power Supplies - External/Internal (Off-Board)           LED Drivers           Package         -           Series         ESS           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Input (Max)         240V           Voltage - Output         28 ~ 42 V           Current - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Manufacturer Part Number	ESS015E-0350-42	
Package         -           Series         ESS           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Output (Max)         240V           Voltage - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Manufacturer	ERP Power, LLC	
Package         -           Series         ESS           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Input (Max)         240V           Voltage - Output         28 ~ 42 V           Current - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series         ESS           Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Input (Max)         240V           Voltage - Output         28 ~ 42 V           Current - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)		LED Drivers	
Type         Constant Current           Topology         AC DC Converter           Number of Outputs         1           Voltage - Input (Min)         220V           Voltage - Input (Max)         240V           Voltage - Output         28 ~ 42 V           Current - Output (Max)         350mA           Power (Watts)         15W           Voltage - Isolation         -           Dimming         ELV, Triac           Features         OCP, OTP, SCP           Ratings         IP64           Operating Temperature         -           Efficiency         87%           Termination Style         Wire Leads           Size / Dimension         3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Package	-	
Topology       AC DC Converter         Number of Outputs       1         Voltage - Input (Min)       220V         Voltage - Input (Max)       240V         Voltage - Output       28 ~ 42 V         Current - Output (Max)       350mA         Power (Watts)       15W         Voltage - Isolation       -         Dimming       ELV, Triac         Features       OCP, OTP, SCP         Ratings       IP64         Operating Temperature       -         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Series	ESS	
Number of Outputs       1         Voltage - Input (Min)       220V         Voltage - Input (Max)       240V         Voltage - Output       28 ~ 42 V         Current - Output (Max)       350mA         Power (Watts)       15W         Voltage - Isolation       -         Dimming       ELV, Triac         Features       OCP, OTP, SCP         Ratings       IP64         Operating Temperature       -         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Type	Constant Current	
Voltage - Input (Min)       220V         Voltage - Input (Max)       240V         Voltage - Output       28 ~ 42 V         Current - Output (Max)       350mA         Power (Watts)       15W         Voltage - Isolation       -         Dimming       ELV, Triac         Features       OCP, OTP, SCP         Ratings       IP64         Operating Temperature       -         Efficiency       87%         Termination Style       Wire Leads         Size / Dimension       3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Topology	AC DC Converter	
Voltage - Input (Max)  Voltage - Output  28 ~ 42 V  Current - Output (Max)  350mA  Power (Watts)  15W  Voltage - Isolation  - Dimming  ELV, Triac  Features  OCP, OTP, SCP  Ratings  IP64  Operating Temperature  Efficiency  87%  Termination Style  Size / Dimension  240V  240V  240V  240V  240V  240V  240V  240V  28 ~ 42 V  28 ~ 42	Number of Outputs	1	
Voltage - Output (Max) 350mA  Power (Watts) 15W  Voltage - Isolation -  Dimming ELV, Triac  Features OCP, OTP, SCP  Ratings IP64  Operating Temperature -  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Voltage - Input (Min)	220V	
Current - Output (Max)  Power (Watts)  15W  Voltage - Isolation  - Dimming  ELV, Triac  Features  OCP, OTP, SCP  Ratings  IP64  Operating Temperature  - Efficiency  87%  Termination Style  Size / Dimension  350mA  350mA  350mA  350mA  15W  Current - Output (Max)  - ELV, Triac  OCP, OTP, SCP  87%  184  185  186  186  187  188  188  188  188  188	Voltage - Input (Max)	240V	
Power (Watts)  15W  Voltage - Isolation  - Dimming  ELV, Triac  Features  OCP, OTP, SCP  Ratings  IP64  Operating Temperature  - Efficiency  87%  Termination Style  Wire Leads  Size / Dimension  15W  - Comparing Temperature  - Size / Dimension  15W  - Comparing Temperature  - Size / Dimension  15W  - Comparing Temperature  - Size / Dimension  15W  - Size /	Voltage - Output	28 ~ 42 V	
Voltage - Isolation  Dimming ELV, Triac  Features OCP, OTP, SCP  Ratings IP64  Operating Temperature -  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Current - Output (Max)	350mA	
Dimming ELV, Triac  Features OCP, OTP, SCP  Ratings IP64  Operating Temperature -  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Power (Watts)	15W	
Features OCP, OTP, SCP  Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Voltage - Isolation	-	
Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Dimming	ELV, Triac	
Operating Temperature -  Efficiency 87%  Termination Style Wire Leads  Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Features	OCP, OTP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Ratings	IP64	
Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Operating Temperature	-	
Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Efficiency	87%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	
			Report errors?

#### ESS015E-0350-42 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ESS015E-0350-42 Payment Methods



















## ESS015E-0350-42 Shipping Methods













If you have any question about ESS015E-0350-42, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com