

ESS020W-1400-14 Information



For Reference Only

Part Number ESS020W-1400-14 Manufacturer ERP Power, LLC

Category Power Supplies - External/Internal (Off-Board)

LED Drivers

Description LED DRIVER CC AC/DC 8-14V 1.4A

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ESS020W-1400-14 Specifications

Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESS Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature -			
Category Power Supplies - External/Internal (Off-Board) LED Drivers Package - Series ESS Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Manufacturer Part Number	ESS020W-1400-14	
LED Drivers Package - Series ESS Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Manufacturer	ERP Power, LLC	
Package - Series ESS Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Category	Power Supplies - External/Internal (Off-Board)	
Series ESS Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)		LED Drivers	
Type Constant Current Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Package	-	
Topology AC DC Converter Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Series	ESS	
Number of Outputs 1 Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Type	Constant Current	
Voltage - Input (Min) 120V Voltage - Input (Max) 277V Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Topology	AC DC Converter	
Voltage - Input (Max) Voltage - Output 8 ~ 14 V Current - Output (Max) 1.4A Power (Watts) Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature Efficiency 87% Termination Style Size / Dimension 277V 8 ~ 14 V Current - Output (Max) 1.4A 20W Current - Output (Max) - ELV, Triac Features OCP, OTP, SCP 87% Wire Leads 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Number of Outputs	1	
Voltage - Output (Max) 1.4A Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Voltage - Input (Min)	120V	
Current - Output (Max) Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Size / Dimension 1.4A 1.4	Voltage - Input (Max)	277V	
Power (Watts) 20W Voltage - Isolation - Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Size / Dimension 20W - 81W ELV, Triac - 82P Wire Leads 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Voltage - Output	8 ~ 14 V	
Voltage - Isolation Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Current - Output (Max)	1.4A	
Dimming ELV, Triac Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Power (Watts)	20W	
Features OCP, OTP, SCP Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Voltage - Isolation	-	
Ratings IP64 Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Dimming	ELV, Triac	
Operating Temperature - Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Features	OCP, OTP, SCP	
Efficiency 87% Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Ratings	IP64	
Termination Style Wire Leads Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Operating Temperature	-	
Size / Dimension 3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	Efficiency	87%	
	Termination Style	Wire Leads	
Report errors?	Size / Dimension	3.30" L x 1.57" W x 0.99" H (83.8mm x 39.9mm x 25.1mm)	
			Report errors?

ESS020W-1400-14 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ESS020W-1400-14 Payment Methods





















ESS020W-1400-14 Shipping Methods













If you have any question about ESS020W-1400-14, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com