

### ESW-107-23-G-D Information

Heisener.com

For Reference Only

Part Number ESW-107-23-G-D

Manufacturer Samtec Inc.

**Category** Connectors, Interconnects

Rectangular Connectors - Headers, Receptacles,

Female Sockets

**Description** ELEVATED SOCKET STRIPS

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# ESW-107-23-G-D Specifications

Manufacturer Part Number         ESW-107-23-G-D           Manufacturer         Samtec Inc.           Category         Connectors, Interconnects           Rectangular Connectors - Headers, Receptacles, Female Sockets           Package         -           Series         ESW           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board           Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20µin (0.51µm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C - 125°C		
Category         Connectors, Interconnects           Package         -           Series         ESW           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20μin (0.51μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C ~ 125°C	Manufacturer Part Number	ESW-107-23-G-D
Package-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Manufacturer	Samtec Inc.
Package         -           Series         ESW           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20µin (0.51µm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C ~ 125°C	Category	Connectors, Interconnects
Series         ESW           Connector Type         Elevated Socket           Contact Type         Forked           Style         Board to Board           Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20μin (0.51μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C ~ 125°C		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20µin (0.51µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Package	-
Contact Type         Forked           Style         Board to Board           Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20μin (0.51μm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C ~ 125°C	Series	ESW
StyleBoard to BoardNumber of Positions14Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Connector Type	Elevated Socket
Number of Positions         14           Number of Positions Loaded         All           Pitch - Mating         0.100" (2.54mm)           Number of Rows         2           Row Spacing - Mating         0.100" (2.54mm)           Mounting Type         Through Hole           Termination         Solder           Fastening Type         Push-Pull           Contact Finish - Mating         Gold           Contact Finish Thickness - Mating         20µin (0.51µm)           Insulation Color         Black           Insulation Height         0.535" (13.60mm)           Contact Length - Post         0.190" (4.83mm)           Operating Temperature         -55°C ~ 125°C	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows2Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Style	Board to Board
Pitch - Mating 0.100" (2.54mm)  Number of Rows 2  Row Spacing - Mating 0.100" (2.54mm)  Mounting Type Through Hole  Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 20µin (0.51µm)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.190" (4.83mm)  Operating Temperature -55°C ~ 125°C	Number of Positions	14
Number of Rows2Row Spacing - Mating $0.100"$ (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating $20\mu in (0.51\mu m)$ Insulation ColorBlackInsulation Height $0.535"$ (13.60mm)Contact Length - Post $0.190"$ (4.83mm)Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Number of Positions Loaded	All
Row Spacing - Mating0.100" (2.54mm)Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating20μin (0.51μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)Contact Length - Post0.190" (4.83mm)Operating Temperature-55°C ~ 125°C	Number of Rows	2
Termination Solder  Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 20 $\mu$ in (0.51 $\mu$ m)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.190" (4.83mm)  Operating Temperature -55°C ~ 125°C	Row Spacing - Mating	0.100" (2.54mm)
Fastening Type Push-Pull  Contact Finish - Mating Gold  Contact Finish Thickness - Mating 20 $\mu$ in (0.51 $\mu$ m)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.190" (4.83mm)  Operating Temperature -55°C ~ 125°C	Mounting Type	Through Hole
Contact Finish - Mating Gold  Contact Finish Thickness - Mating 20 $\mu$ in (0.51 $\mu$ m)  Insulation Color Black  Insulation Height 0.535" (13.60mm)  Contact Length - Post 0.190" (4.83mm)  Operating Temperature -55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Mating $20\mu in (0.51\mu m)$ Insulation Color Black Insulation Height $0.535'' (13.60mm)$ Contact Length - Post $0.190'' (4.83mm)$ Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Fastening Type	Push-Pull
Insulation ColorBlackInsulation Height $0.535"$ ( $13.60mm$ )Contact Length - Post $0.190"$ ( $4.83mm$ )Operating Temperature $-55^{\circ}$ C ~ $125^{\circ}$ C	Contact Finish - Mating	Gold
Insulation Height $0.535" (13.60 \text{mm})$ Contact Length - Post $0.190" (4.83 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Contact Finish Thickness - Mating	20μin (0.51μm)
Contact Length - Post $0.190" (4.83 \text{mm})$ Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Color	Black
Operating Temperature $-55^{\circ}\text{C} \sim 125^{\circ}\text{C}$	Insulation Height	0.535" (13.60mm)
	Contact Length - Post	0.190" (4.83mm)
AND LAND AND AND AND AND AND AND AND AND AND	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Gold
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?

#### ESW-107-23-G-D Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ESW-107-23-G-D Payment Methods



















## ESW-107-23-G-D Shipping Methods













If you have any question about ESW-107-23-G-D, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com