

ESW-126-23-S-S

ESW-126-23-S-S Information

Heisener.com	Part Number	ESW-126-23-S-S	
	Manufacturer	Samtec Inc.	
	Category	Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets	
	Description	ELEVATED SOCKET STRIPS	
	Package	-	回购受税
For Reference Only		For the pricing/inventory/lead time, please contact	
		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality


Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ESW-126-23-S-S Specifications

Manufacturer Part NumberESW-126-23-S-SManufacturerSamtee Inc.CategoryConnectors, InterconnectsRectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions26Number of Rostions Loaded1010° (254mm)Number of Rosting0.100° (254mm)Number of Rosting0.100° (254mm)Row Spacing - MatingSolderTerninationSolderForting TypeGoldContact Finish - MatingGoldContact Finish - MatingSolderFastening TypeBoardStation ColorGoldStation Finish - MatingSolderFastening TypeBoardStation ColorBackInsulation ColorBiackInsulation Finish - Mating0.53° (13.60mm)Contact Length - Post0.100° (48.3mm)		
Category Connectors, Interconnects Rectangular Connectors - Headers, Receptacles, Female Sockets Package - Series ESW Connector Type Elevated Socket Contact Type Forked Style Board to Board Number of Positions 26 Number of Positions Loaded All Pitch - Mating 0.100" (2.54mm) Number of Rows 1 Row Spacing - Mating - Mounting Type Through Hole Termination Solder Fastening Type Qual Contact Finish - Mating Gold Contact Finish - Mating Solder Fastening Type Board IO.00" (2.54mm) Fastening Type Solder Forther Solder Solder Forther	Manufacturer Part Number	ESW-126-23-S-S
Rectangular Connectors - Headers, Receptacles, Female SocketsPackage-SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderFastening TypeGoldContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Manufacturer	Samtec Inc.
Package-SeriesESWConactor TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeOlderFastening TypeGoldContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBiackInsulation Height0.535" (13.60mm)	Category	Connectors, Interconnects
SeriesESWConnector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFastening TypeSolderContact Finish - MatingGoldContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.535" (13.60mm)		Rectangular Connectors - Headers, Receptacles, Female Sockets
Connector TypeElevated SocketContact TypeForkedStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleFareninationSolderFastening TypeOudContact Finish - MatingGoldContact Finish Thickness - MatingSupin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Package	-
Contact TypeForkedStyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Series	ESW
StyleBoard to BoardNumber of Positions26Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldInsulation ColorBlackInsulation Height0.535" (13.60mm)	Connector Type	Elevated Socket
Yumber of Positions26Number of Positions LoadedAllPitch - Mating0.100° (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Contact Type	Forked
Number of Positions LoadedAllPitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Style	Board to Board
Pitch - Mating0.100" (2.54mm)Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldSoluri O.76µm)Juni O.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Number of Positions	26
Number of Rows1Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish - MatingJupin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60µm)	Number of Positions Loaded	All
Row Spacing - Mating-Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Pitch - Mating	0.100" (2.54mm)
Mounting TypeThrough HoleTerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Number of Rows	1
TerminationSolderFastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Row Spacing - Mating	-
Fastening TypePush-PullContact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Mounting Type	Through Hole
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Termination	Solder
Contact Finish Thickness - Mating30μin (0.76μm)Insulation ColorBlackInsulation Height0.535" (13.60mm)	Fastening Type	Push-Pull
Insulation Color Black Insulation Height 0.535" (13.60mm)	Contact Finish - Mating	Gold
Insulation Height 0.535" (13.60mm)	Contact Finish Thickness - Mating	30µin (0.76µm)
	Insulation Color	Black
Contact Length - Post 0.190" (4.83mm)	Insulation Height	0.535" (13.60mm)
	Contact Length - Post	0.190" (4.83mm)
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Operating Temperature	-55°C ~ 125°C
Material Flammability Rating UL94 V-0	Material Flammability Rating	UL94 V-0

Contact Finish - Post	Tin
Mated Stacking Heights	-
Ingress Protection	-
Features	-
	Report errors?





Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ESW-126-23-S-S, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com