

# ETMA150667UC-P51-WP

### ETMA150667UC-P51-WP Information



For Reference Only

Part Number ETMA150667UC-P51-WP

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

**Description** AC/DC DESKTOP ADAPTER 15V 110W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## ETMA150667UC-P51-WP Specifications

Manufacturer Part Number         ETMA150667UC-P51-WP           Manufacturer         CUI Inc.           Category         Power Supplies - External/Internal (Off-Board)           Reckage         -           Series         ETMA 110W           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         6.67A           Power (Watts)         100W           No Load Power Consumption         300mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Desktop, Wall Adapters           Package         -           Series         ETMA 110W           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         6.67A           Power (Watts)         100W           No Load Power Consumption         300mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Manufacturer Part Number	ETMA150667UC-P51-WP
Package         -           Series         ETMA 110W           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         6.67A           Power (Watts)         100W           No Load Power Consumption         300mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Manufacturer	CUI Inc.
Package         -           Series         ETMA 110W           Region Utilized         North America           Form         Desktop (Class I)           Input Type         Cord           Voltage - Input         90 ~ 264 VAC           Voltage - Output         15V           Current - Output (Max)         6.67A           Power (Watts)         100W           No Load Power Consumption         300mW (Max)           Polarization         -           Applications         Medical           Efficiency         Level V           Operating Temperature         0°C ~ 40°C           Output Connector         Power DIN, 4 Pin           Size / Dimension         6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETMA 110WRegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input90 ~ 264 VACVoltage - Output15VCurrent - Output (Max)6.67APower (Watts)100WNo Load Power Consumption300mW (Max)Polarization-ApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorPower DIN, 4 PinSize / Dimension6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)		AC DC Desktop, Wall Adapters
Region Utilized North America Form Desktop (Class I)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 6.67A  Power (Watts) 100W  No Load Power Consumption 300mW (Max)  Polarization - Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Package	-
Form Desktop (Class I)  Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 6.67A  Power (Watts) 100W  No Load Power Consumption 300mW (Max)  Polarization -  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Series	ETMA 110W
Input Type Cord  Voltage - Input 90 ~ 264 VAC  Voltage - Output 15V  Current - Output (Max) 6.67A  Power (Watts) 100W  No Load Power Consumption 300mW (Max)  Polarization -  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Region Utilized	North America
Voltage - Input  90 ~ 264 VAC  Voltage - Output  15V  Current - Output (Max)  6.67A  Power (Watts)  100W  No Load Power Consumption  300mW (Max)  Polarization  - Applications  Medical  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  90 ~ 264 VAC	Form	Desktop (Class I)
Voltage - Output  Current - Output (Max)  6.67A  Power (Watts)  100W  No Load Power Consumption  300mW (Max)  Polarization  -  Applications  Medical  Efficiency  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  15V  6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Input Type	Cord
Current - Output (Max) 6.67A  Power (Watts) 100W  No Load Power Consumption 300mW (Max)  Polarization - Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts)  100W  No Load Power Consumption  300mW (Max)  Polarization  - Applications  Medical  Efficiency  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  Size / Dimension  100W  Max)  - Consumption  Medical  Level V  Operating Temperature  0°C ~ 40°C  Output Connector  Power DIN, 4 Pin  6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Voltage - Output	15V
No Load Power Consumption 300mW (Max)  Polarization -  Applications Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Current - Output (Max)	6.67A
Polarization - Medical  Efficiency Level V  Operating Temperature 0°C ~ 40°C  Output Connector Power DIN, 4 Pin  Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Power (Watts)	100W
Applications Medical Efficiency Level V   Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin   Size / Dimension $6.69^{\circ}\text{L} \times 2.55^{\circ}\text{W} \times 1.52^{\circ}\text{H} (170.0 \text{mm} \times 64.8 \text{mm} \times 38.5 \text{mm})$	No Load Power Consumption	300mW (Max)
Efficiency Level V  Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin  Size / Dimension $6.69^{\circ}\text{L x } 2.55^{\circ}\text{W x } 1.52^{\circ}\text{H } (170.0\text{mm x } 64.8\text{mm x } 38.5\text{mm})$	Polarization	-
Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Power DIN, 4 Pin Size / Dimension $6.69^{\circ}\text{L} \times 2.55^{\circ}\text{W} \times 1.52^{\circ}\text{H} (170.0\text{mm} \times 64.8\text{mm} \times 38.5\text{mm})$	Applications	Medical
Output Connector Power DIN, 4 Pin Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Efficiency	Level V
Size / Dimension 6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)	Operating Temperature	$0^{\circ}\text{C} \sim 40^{\circ}\text{C}$
	Output Connector	Power DIN, 4 Pin
Report errors?	Size / Dimension	6.69" L x 2.55" W x 1.52" H (170.0mm x 64.8mm x 38.5mm)
		Report errors?

#### ETMA150667UC-P51-WP Guarantees



## **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### ETMA150667UC-P51-WP Payment Methods



















## ETMA150667UC-P51-WP Shipping Methods













If you have any question about ETMA150667UC-P51-WP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com