

ETMA240250UD-P6RP-IC

ETMA240250UD-P6RP-IC Information



For Reference Only

Part Number ETMA240250UD-P6RP-IC

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 24V 60W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ETMA240250UD-P6RP-IC Specifications

Manufacturer Part NumberETMA240250UD-P6RP-ICManufacturerCUI Inc.CategoryPower Supplies - External/Internal (Off-Board)AC DC Desktop, Wall AdaptersPackage-SeriesETMA 60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETMA 60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Manufacturer Part Number	ETMA240250UD-P6RP-IC
Package - Series ETMA 60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Manufacturer	CUI Inc.
Package - Series ETMA 60W Region Utilized International Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETMA 60WRegion UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)		AC DC Desktop, Wall Adapters
Region UtilizedInternationalFormDesktop (Class II)Input TypeCord (Sold Separately)Voltage - Input90 ~ 264 VACVoltage - Output24VCurrent - Output (Max)2.5APower (Watts)60WNo Load Power Consumption300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Package	-
Form Desktop (Class II) Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Series	ETMA 60W
Input Type Cord (Sold Separately) Voltage - Input 90 ~ 264 VAC Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Region Utilized	International
Voltage - Input $90 \sim 264 \text{ VAC}$ Voltage - Output 24V Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20°L x 2.28° W x 1.20° H (132.0mm x 58.0mm x 30.5mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 2.5A Power (Watts) No Load Power Consumption Polarization Polarization Applications Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 24V 24V 24V 24V 24V 25A 60W Max) Power (Watts) Agoma W (Max) Positive Center Medical Level V Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Input Type	Cord (Sold Separately)
Current - Output (Max) 2.5A Power (Watts) 60W No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Voltage - Input	90 ~ 264 VAC
Power (Watts) $60W$ No Load Power Consumption $300mW$ (Max)PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 5.20 " L x 2.28 " W x 1.20 " H ($132.0mm$ x $58.0mm$ x $30.5mm$)	Voltage - Output	24V
No Load Power Consumption 300mW (Max) Polarization Positive Center Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Current - Output (Max)	2.5A
PolarizationPositive CenterApplicationsMedicalEfficiencyLevel VOperating Temperature 0° C ~ 40° COutput ConnectorBarrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension 5.20° L x 2.28° W x 1.20° H (132.0 mm x 58.0 mm x 30.5 mm)	Power (Watts)	60W
Applications Medical Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	No Load Power Consumption	300mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $5.20^{\circ}\text{L} \times 2.28^{\circ}\text{W} \times 1.20^{\circ}\text{H} (132.0 \text{mm} \times 58.0 \text{mm} \times 30.5 \text{mm})$	Polarization	Positive Center
	Applications	Medical
Output Connector Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Efficiency	Level V
Size / Dimension 5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug R/A, 2.5mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	5.20" L x 2.28" W x 1.20" H (132.0mm x 58.0mm x 30.5mm)
report circus.		Report errors?

ETMA240250UD-P6RP-IC Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ETMA240250UD-P6RP-IC Payment Methods



















ETMA240250UD-P6RP-IC Shipping Methods













If you have any question about ETMA240250UD-P6RP-IC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com