

Heisener.com

ETSA120500UC-P5RP-SZ

ETSA120500UC-P5RP-SZ Information

Part Number ETSA120500UC-P5RP-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 60W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ETSA120500UC-P5RP-SZ Specifications

| Manufacturer Part Number ETSA120500UC-P5RP-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | | |
|---|---------------------------|---|
| Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Manufacturer Part Number | ETSA120500UC-P5RP-SZ |
| Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Manufacturer | CUI Inc. |
| Package - Series ETSA-U Region Utilized North America Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Category | Power Supplies - External/Internal (Off-Board) |
| SeriesETSA-URegion UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | | AC DC Desktop, Wall Adapters |
| Region UtilizedNorth AmericaFormDesktop (Class I)Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57° L x 1.97° W x 1.22° H (116.0mm x 50.0mm x 31.0mm) | Package | - |
| Form Desktop (Class I) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Series | ETSA-U |
| Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug R/A, 2.1mm I.D. $\times 5.5\text{mm}$ O.D. $\times 9.5\text{mm}$ Size / Dimension 4.57 " L $\times 1.97$ " W $\times 1.22$ " H ($116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm}$) | Region Utilized | North America |
| Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Form | Desktop (Class I) |
| Voltage - Output Current - Output (Max) 5A Power (Watts) No Load Power Consumption Polarization Applications Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Input Type | Cord |
| Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Voltage - Input | 85 ~ 264 VAC |
| Power (Watts) $60W$ No Load Power Consumption $500mW$ (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}C \sim 40^{\circ}C$ Output ConnectorBarrel Plug R/A, $2.1mm$ I.D. x $5.5mm$ O.D. x $9.5mm$ Size / Dimension 4.57 " L x 1.97 " W x 1.22 " H ($116.0mm$ x $50.0mm$ x $31.0mm$) | Voltage - Output | 12V |
| No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$ | Current - Output (Max) | 5A |
| Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$ | Power (Watts) | 60W |
| Applications ITE (Commercial) Efficiency Level V Operating Temperature 0° C ~ 40° C Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57° L x 1.97° W x 1.22° H (116.0mm x 50.0 mm x 31.0 mm) | No Load Power Consumption | 500mW (Max) |
| Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm})$ | Polarization | Positive Center |
| Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \text{ x } 1.97^{\circ}\text{ W x } 1.22^{\circ}\text{H} (116.0\text{mm x } 50.0\text{mm x } 31.0\text{mm})$ | Applications | ITE (Commercial) |
| Output Connector Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Efficiency | Level V |
| Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) | Operating Temperature | 0°C ~ 40°C |
| | Output Connector | Barrel Plug R/A, 2.1mm I.D. x 5.5mm O.D. x 9.5mm |
| | Size / Dimension | 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm) |
| Report errors? | | Report errors? |

ETSA120500UC-P5RP-SZ Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ETSA120500UC-P5RP-SZ Payment Methods



















ETSA120500UC-P5RP-SZ Shipping Methods













If you have any question about ETSA120500UC-P5RP-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com