

ETSA120500UDC-P5P-SZ

ETSA120500UDC-P5P-SZ Information



For Reference Only

Part Number ETSA120500UDC-P5P-SZ

Manufacturer CUI Inc.

Category Power Supplies - External/Internal (Off-Board)

AC DC Desktop, Wall Adapters

Description AC/DC DESKTOP ADAPTER 12V 60W

Package

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ETSA120500UDC-P5P-SZ Specifications

Manufacturer Part Number ETSA120500UDC-P5P-SZ Manufacturer CUI Inc. Category Power Supplies - External/Internal (Off-Board) Package - Series ETSA Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Desktop, Wall Adapters Package - Series ETSA Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer Part Number	ETSA120500UDC-P5P-SZ
Package - Series ETSA Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1 mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Manufacturer	CUI Inc.
Package - Series ETSA Region Utilized North America Form Desktop (Class II) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Category	Power Supplies - External/Internal (Off-Board)
SeriesETSARegion UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)		AC DC Desktop, Wall Adapters
Region UtilizedNorth AmericaFormDesktop (Class II)Input TypeCordVoltage - Input85 ~ 264 VACVoltage - Output12VCurrent - Output (Max)5APower (Watts)60WNo Load Power Consumption500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature0°C ~ 40°COutput ConnectorBarrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mmSize / Dimension4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Package	-
Form Desktop (Class II) Input Type Cord Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Series	ETSA
Input TypeCordVoltage - Input $85 \sim 264 \text{ VAC}$ Voltage - Output 12V Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max)PolarizationPositive CenterApplicationsITE (Commercial)EfficiencyLevel VOperating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output ConnectorBarrel Plug, 2.1mm I.D. $x 5.5\text{mm}$ O.D. $x 9.5\text{mm}$ Size / Dimension 4.57 " L $x 1.97$ " W $x 1.22$ " H (116.0mm x 50.0mm x 31.0mm)	Region Utilized	North America
Voltage - Input 85 ~ 264 VAC Voltage - Output 12V Current - Output (Max) 5A Power (Watts) No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Form	Desktop (Class II)
Voltage - Output Current - Output (Max) 5A Power (Watts) No Load Power Consumption Polarization Applications Efficiency Operating Temperature O°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Input Type	Cord
Current - Output (Max) 5A Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Voltage - Input	85 ~ 264 VAC
Power (Watts) 60W No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature 0°C ~ 40°C Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Voltage - Output	12V
No Load Power Consumption 500mW (Max) Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57'' \text{ L x 1.97'' W x 1.22'' H (116.0mm x 50.0mm x 31.0mm)}$	Current - Output (Max)	5A
Polarization Positive Center Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0 \text{mm} \times 50.0 \text{mm} \times 31.0 \text{mm})$	Power (Watts)	60W
Applications ITE (Commercial) Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm})$	No Load Power Consumption	500mW (Max)
Efficiency Level V Operating Temperature $0^{\circ}\text{C} \sim 40^{\circ}\text{C}$ Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension $4.57^{\circ}\text{L} \times 1.97^{\circ}\text{W} \times 1.22^{\circ}\text{H} (116.0\text{mm} \times 50.0\text{mm} \times 31.0\text{mm})$	Polarization	Positive Center
	Applications	ITE (Commercial)
Output Connector Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Efficiency	Level V
Size / Dimension 4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)	Operating Temperature	0°C ~ 40°C
	Output Connector	Barrel Plug, 2.1mm I.D. x 5.5mm O.D. x 9.5mm
Report errors?	Size / Dimension	4.57" L x 1.97" W x 1.22" H (116.0mm x 50.0mm x 31.0mm)
		Report errors?

ETSA120500UDC-P5P-SZ Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ETSA120500UDC-P5P-SZ Payment Methods



















ETSA120500UDC-P5P-SZ Shipping Methods













If you have any question about ETSA120500UDC-P5P-SZ, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com